


Safety data sheet according to 1907/2006/EC, Article 31



 Hazard-determining components of labelling: methyl acetate acetone

(Contd. on page 2)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.05.2023

Version number 13 (replaces version 12)

Revision: 06.05.2023

(Contd. of page 1)

Trade name: UHU AP CN 5KG*1 DE

· Hazard statements

H225 Highly flammable liquid and vapour.

- H336 May cause drowsiness or dizziness.
- · Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing vapours.
- P501 Dispose of contents/container in accordance with national regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

 Dangerous components: 		
CAS: 79-20-9 EINECS: 201-185-2 Index number: 607-021-00-X Reg.nr.: 01-2119459211-47- XXXX	methyl acetate Flam. Liq. 2, H225;	50-100%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43	ethanol	≥2.5-<10%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49- XXXX	acetone Flam. Liq. 2, H225;	≥2.5-<10%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: No special measures required.

• After inhalation:

Supply fresh air; consult doctor in case of complaints.

- No special measures required.
- After skin contact: Generally the product does not irritate the skin.

(Contd. on page 3)

EU-EN



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.05.2023

Version number 13 (replaces version 12)

Revision: 06.05.2023

Trade name: UHU AP CN 5KG*1 DE

(Contd. of page 2)

· After eye contact: Rinse opened eye for several minutes under running water.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
- Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- **Information about fire and explosion protection:** Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Storage class: 3

(Contd. on page 4)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.05.2023

Version number 13 (replaces version 12)

Revision: 06.05.2023

Trade name: UHU AP CN 5KG*1 DE

• 7.3 Specific end use(s) No further relevant information available.

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

67-64-1 ad		
	ng-term value: 1210 mg/m³, 500 ppm	
DNELS		
	ethyl acetate	
Oral	Consumer, oral, longterm exposition	44 mg/kg bw/day
Dermal	Consumer, dermal, longterm exposition	000
Inhalative	Consumer DNEL, acute inhalation	mg/m³ (rat)
		mg/m³ (rabbit)
	Consumer, inhalation, longterm expos	ition 131 mg/m ³
64-17-5 et		
Oral	Consumer, oral, longterm exposition	87 mg/kg bw/day
Dermal	Consumer, dermal, longterm exposition	
Inhalative	Consumer, inhalation, longterm expos	ition 950 mg/m ³
67-64-1 ad		
Oral	Consumer, oral, longterm exposition	62 mg/kg bw/day
Dermal	Consumer, dermal, longterm exposition	on 62 mg/kg bw/day
Inhalative	Consumer, inhalation, longterm expos	ition 200 mg/m ³
PNECs		
79-20-9 m	ethyl acetate	
Fresh wate	er 0.12 mg/l	
Marine wa	ter 0.012 mg/l	
Soil	0.0416 mg/kg	
64-17-5 et	hanol	
Fresh wate	er 0.96 mg/l	
Marine wa	ter 0.79 mg/l	
Soil	0.63 mg/kg	
67-64-1 ad		
Fresh wate	er 10.6 mg/l	
Marine wa	ter 1.06 mg/l	
Soil	29.5 mg/kg	
Additiona	I information: The lists valid during th	e making were used as basis.
8.2 Expos Appropria	ure controls te engineering controls No further d protection measures, such as pers	ata; see item 7.

EU-EN



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.05.2023

Version number 13 (replaces version 12)

Revision: 06.05.2023

(Contd. of page 4)

Trade name: UHU AP CN 5KG*1 DE

Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols.

- · Respiratory protection: Not required.
- Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves Recommended thickness of the material: > 0,12 mm Nitrile rubber, NBR
- Penetration time of glove material For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).
- Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

9.1 Information on basic physical and ch	emical properties	
General Information		
Physical state	Fluid	
Colour:	Colourless	
Odour:	Characteristic	
Odour threshold:	Not determined.	
Melting point/freezing point:	Undetermined.	
Boiling point or initial boiling point and		
boiling range	55.8-56.6 °C	
Flammability	Highly flammable.	
Lower and upper explosion limit		
Lower:	3.1 Vol %	
Upper:	16 Vol %	
Flash point:	-13 °C	
Ignition temperature:	425 °C	
Decomposition temperature:	Not determined.	
pH	Not determined.	
Viscosity:		
Kinematic viscosity	Not determined.	
Dynamic at 20 °C:	4400 mPas	
Solubility		
water:	Not miscible or difficult to mix.	
Partition coefficient n-octanol/water (log	······	
value)	Not determined.	
Vapour pressure at 20 °C:	220 hPa	



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.05.2023

Version number 13 (replaces version 12)

Revision: 06.05.2023

Trade name: UHU AP CN 5KG*1 DE

	(Contd. of page
Density and/or relative density	
Density at 20 °C:	0.987 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
· 9.2 Other information	All relevant physical data were determined for the
	mixture. All non-determined data are no
	measurable or not relevant for the
	characterization of the mixture.
Appearance:	
· Form:	Fluid
 Important information on protection of heat and an apfatulation 	lith
and environment, and on safety.	Draduat is not califianiting
 Auto-ignition temperature: Explosive properties: 	Product is not selfigniting. Product is not explosive. However, formation of
Explosive properties:	explosive air/vapour mixtures are possible.
· Solvent content:	explosive all/vapour mixtures are possible.
· Organic solvents:	65.8 %
· Water:	0.4 %
· VOC (EC)	65.79 %
· Solids content:	33.8 %
[•] Change in condition	00.0 //
· Evaporation rate	Not determined.
Information with regard to physical haza	ard
classes	
· Explosives	Void
· Flammable gases	Void
Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
 Self-reactive substances and mixtures 	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
	Void
Oxidising liquids	N / · · ·
Oxidising solids	Void
· Oxidising solids · Organic peroxides	Void
Oxidising solids	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

(Contd. on page 7)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.05.2023

Version number 13 (replaces version 12)

Revision: 06.05.2023

Trade name: UHU AP CN 5KG*1 DE

· 10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

• **10.3 Possibility of hazardous reactions** No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

• 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 • Acute toxicity Based on available data, the classification criteria are not met.

 LD/LC50 values relevant for classification: 	

79-20-9 m	79-20-9 methyl acetate			
Oral	LD50	3705 mg/kg (rabbit)		
64-17-5 et	64-17-5 ethanol			
Oral	LD50	7060 mg/kg (rat)		
Inhalative	LC50/4 h	7060 mg/kg (rat) 20000 mg/l (rat)		
67-64-1 ac	atona	·		

67-64-1 acetone

Oral L	_D50	5800	mg/kg	(rat)
--------	------	------	-------	-------

Dermal LD50 20000 mg/kg (rabbit)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity: No further relevant information available.

- 12.2 Persistence and degradability No further relevant information available.
- \cdot 12.3 Bioaccumulative potential No further relevant information available.

(Contd. on page 8) EU-EN

(Contd. of page 6)

Is: No further relevant sition products: No



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.05.2023

Version number 13 (replaces version 12)

Revision: 06.05.2023

Trade name: UHU AP CN 5KG*1 DE

(Contd. of page 7)

• **12.4 Mobility in soil** No further relevant information available.

- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informa	tion	
 14.1 UN number or ID number ADR/ADN, IMDG, IATA 	UN1133	
 14.2 UN proper shipping name ADR/ADN IMDG, IATA 	1133 ADHESIVES ADHESIVES	
 • 14.3 Transport hazard class(es) • ADR/ADN 		
· Class	3 (F1) Flammable liquids.	
		(Contd. on page 9)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.05.2023

Version number 13 (replaces version 12)

Revision: 06.05.2023

Trade name: UHU AP CN 5KG*1 DE

	(Contd. of page
Label	3
· IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR/ADN, IMDG, IATA	III
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	
· EMS Number: · Stowage Category	F-E,S-D A
• 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
 Transport/Additional information: Quantity limitations 	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR/ADN · Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
,	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100
· Transport category	ml 3
[•] Tunnel restriction code	E
·IMDG	
· Limited quantities (LQ)	5L
 Excepted quantities (EQ) 	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
· UN "Model Regulation":	UN 1133 ADHESIVES, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t

(Contd. on page 10) EU-EN-



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.05.2023

Version number 13 (replaces version 12)

Revision: 06.05.2023

Trade name: UHU AP CN 5KG*1 DE

(Contd. of page 9)

3

3

• Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t • REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

67-64-1 acetone

· Regulation (EC) No 273/2004 on drug precursors

67-64-1 acetone

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

67-64-1 acetone

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

Flammable liquids	Bridging principles		
	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.		

• Department issuing SDS: UHU QESH

- · Contact: UHU QESH
- Date of previous version: 15.01.2022
- · Version number of previous version: 12
- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

(Contd. on page 11)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.05.2023

Version number 13 (replaces version 12)

Revision: 06.05.2023

Trade name: UHU AP CN 5KG*1 DE

(Contd. of page 10)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

** Data compared to the previous version altered.

EU-EN