

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 28

Revision: 26.06.2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
  - **Trade name: UHU KONTAKT Kraftkleber gel (Tube) < 350 g**
  - **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
  - **Application of the substance / the mixture** Adhesives
  - **1.3 Details of the supplier of the safety data sheet**
  - **Manufacturer/Supplier:**  
UHU GmbH & Co.KG  
Herrmannstraße 7  
D-77815 Bühl (Baden)  
Tel.: 0049-(0)7223-284-0  
email: sds@uhu.boltongroup.com
  - Fax: 0049-(0)7223-284-245
  - **Further information obtainable from:** UHU QESH
  - **1.4 Emergency telephone number:**  
Tel.: + 49 (0) 30/19240 (Notruf)  
Tel.: + 49 (0) 72 23/28 40
- England and Wales (NHS Direct) 111  
Schottland (NHS 24) 111

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2          H225 Highly flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2   H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
STOT SE 3	H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 28

Revision: 26.06.2019

**Trade name: UHU KONTAKT Kraftkleber gel (Tube) < 350 g**

(Contd. of page 1)

**Hazard pictograms**


GHS02 GHS07 GHS09

**Signal word** Danger

**Hazard-determining components of labelling:**

ethyl acetate

heptane

**Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from open flames. - No smoking.

P261 Avoid breathing vapours.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with national regulations.

**Additional information:**

Contains Rosin. May produce an allergic reaction.

**2.3 Other hazards**
**Results of PBT and vPvB assessment**
**PBT:** Not applicable.

**vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**
**3.2 Mixtures**
**Description:**

Mixture of substances listed below with nonhazardous additions.

Adhesive

(Contd. on page 3)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 28

Revision: 26.06.2019

**Trade name: UHU KONTAKT Kraftkleber gel (Tube) < 350 g**

(Contd. of page 2)

**Dangerous components:**

CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-XXXX	ethyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	25-50%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33-005	heptane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
CAS: 8050-09-7 EINECS: 232-475-7 Reg.nr.: 01-2119480418-32-xxxx	Rosin ⚠ Skin Sens. 1, H317	<1%
CAS: 68610-51-5 EINECS: 271-867-2	phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene ⚠ Repr. 2, H361d	<1%

 · **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

**4.1 Description of first aid measures**

 · **General information:** No special measures required.

**After inhalation:**

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

 · **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

 · **After swallowing:** Do not induce vomiting; call for medical help immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### SECTION 5: Firefighting measures

**5.1 Extinguishing media**
**Suitable extinguishing agents:**

 CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

 · **For safety reasons unsuitable extinguishing agents:** Water with full jet

**5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Hydrogen chloride (HCl)

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 28

Revision: 26.06.2019

**Trade name: UHU KONTAKT Kraftkleber gel (Tube) < 350 g**

(Contd. of page 3)

- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Send for recovery or disposal in suitable receptacles.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

- **Additional information about design of technical facilities:** No further data; see item 7.  
(Contd. on page 5)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 28

Revision: 26.06.2019

**Trade name: UHU KONTAKT Kraftkleber gel (Tube) < 350 g**

(Contd. of page 4)

**· 8.1 Control parameters**
**· Ingredients with limit values that require monitoring at the workplace:**
**141-78-6 ethyl acetate**

IOELV (EU)	Short-term value: 1468 mg/m <sup>3</sup> , 400 ppm Long-term value: 734 mg/m <sup>3</sup> , 200 ppm
AGW (Germany)	Long-term value: 730 mg/m <sup>3</sup> , 200 ppm 2(I);DFG, EU, Y

**8050-09-7 Rosin**

MAK (Germany)	vgl.Abschn.IV
---------------	---------------

**· DNELs**
**141-78-6 ethyl acetate**

Oral	Consumer DNEL, chronic effect oral	4.5 mg/kg ( )
Dermal	Consumer DNEL, chronic effect dermal	37 mg/kg ( )
Inhalative	Consumer DNEL, acute inhalation	734 mg/m <sup>3</sup> ( )
	Verbraucher, Chronische Wirkungen, Einatmen	367 mg/m <sup>3</sup> ( )

**heptane**

Oral	Consumer DNEL, longterm oral	149 mg/kg bw/day
Dermal	Consumer DNEL, longterm dermal	149 mg/kg bw/day
Inhalative	Consumer DNEL, longterm inhalation	477 mg/m <sup>3</sup>

**8050-09-7 Rosin**

Oral	Consumer DNEL, longterm oral	10 mg/kg bw/day (.)
Dermal	Consumer DNEL, longterm dermal	10 mg/kg bw/day (.)
Inhalative	Consumer DNEL, longterm inhalation	35 mg/m <sup>3</sup> (.)

**· PNECs**
**141-78-6 ethyl acetate**

PNEC Fresh water	0.24 mg/l ( )
PNEC Marine water	0.024 mg/l ( )
PNEC Soil	0.148 mg/kg ( )

**heptane**

PNEC Fresh water	mg/l
PNEC Marine water	mg/l
PNEC Soil	mg/kg

**8050-09-7 Rosin**

PNEC Fresh water	0.0016 mg/l (.)
PNEC Marine water	0.0016 mg/l (.)

**· Additional information:** The lists valid during the making were used as basis.

(Contd. on page 6)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 28

Revision: 26.06.2019

**Trade name: UHU KONTAKT Kraftkleber gel (Tube) < 350 g**

(Contd. of page 5)

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

· **Material of gloves**

glove material: butyl rubber

thickness of the glove material: 0,6 - 0,8 mm

breakthrough time (maximum wearing time): 60 - 120 min.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Goggles recommended during refilling



Tightly sealed goggles

Goggles recommended during refilling

EU-EN

(Contd. on page 7)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 28

Revision: 26.06.2019

**Trade name: UHU KONTAKT Kraftkleber gel (Tube) < 350 g**

(Contd. of page 6)

### SECTION 9: Physical and chemical properties

**· 9.1 Information on basic physical and chemical properties**
**· General Information**
**· Appearance:**

<b>Form:</b>	Fluid
<b>Colour:</b>	According to product specification

<b>· Odour:</b>	Characteristic
-----------------	----------------

<b>· Odour threshold:</b>	Not determined.
---------------------------	-----------------

<b>· pH-value:</b>	Not determined.
--------------------	-----------------

**· Change in condition**

<b>  Melting point/freezing point:</b>	Undetermined.
--	---------------

<b>  Initial boiling point and boiling range:</b>	77-78 °C
---	----------

<b>· Flash point:</b>	-4 °C
-----------------------	-------

<b>· Flammability (solid, gas):</b>	Not applicable.
-------------------------------------	-----------------

<b>· Ignition temperature:</b>	460 °C
--------------------------------	--------

<b>· Decomposition temperature:</b>	Not determined.
-------------------------------------	-----------------

<b>· Auto-ignition temperature:</b>	Product is not selfigniting.
-------------------------------------	------------------------------

<b>· Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
--------------------------------	---

**· Explosion limits:**

<b>  Lower:</b>	2.1 Vol %
-----------------	-----------

<b>  Upper:</b>	11.5 Vol %
-----------------	------------

<b>· Vapour pressure at 20 °C:</b>	97 hPa
------------------------------------	--------

<b>· Density at 20 °C:</b>	0.895 g/cm <sup>3</sup>
----------------------------	-------------------------

<b>· Relative density</b>	Not determined.
---------------------------	-----------------

<b>· Vapour density</b>	Not determined.
-------------------------	-----------------

<b>· Evaporation rate</b>	Not determined.
---------------------------	-----------------

**· Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

<b>· Partition coefficient: n-octanol/water:</b>	Not determined.
--	-----------------

**· Viscosity:**

<b>  Dynamic at 20 °C:</b>	20000 mPas
----------------------------	------------

<b>  Kinematic:</b>	Not determined.
---------------------	-----------------

**· Solvent content:**

<b>  Organic solvents:</b>	74.0 %
----------------------------	--------

<b>  Water:</b>	0.1 %
-----------------	-------

<b>  VOC (EC)</b>	73.95 %
-------------------	---------

(Contd. on page 8)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 28

Revision: 26.06.2019

**Trade name: UHU KONTAKT Kraftkleber gel (Tube) < 350 g**

(Contd. of page 7)

<b>Solids content:</b> · <b>9.2 Other information</b>	25.9 % All relevant physical data were determined for the mixture. All non determined data are not measurably or not relevant for the characterization of the mixture.
--	---

#### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

#### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

##### · LD/LC50 values relevant for classification:

##### 141-78-6 ethyl acetate

Oral	LD50	5620 mg/kg (rabbit)
Inhalative	LC50/4 h	1600 mg/l (rat)

##### 68610-51-5 phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene

Oral	LD50	16000 mg/kg (rat)
------	------	-------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

EU-EN

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 28

Revision: 26.06.2019

**Trade name: UHU KONTAKT Kraftkleber gel (Tube) < 350 g**

(Contd. of page 8)

**SECTION 12: Ecological information**

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms  
Do not allow product to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
Disposal must be made according to official regulations.

· **European waste catalogue**

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
-----------	--

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1133
- **14.2 UN proper shipping name**

(Contd. on page 10)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 28

Revision: 26.06.2019

**Trade name: UHU KONTAKT Kraftkleber gel (Tube) < 350 g**

(Contd. of page 9)

<ul style="list-style-type: none"> <li>· ADR</li> <li>· IMDG</li> <li>· IATA</li> </ul>	1133 ADHESIVES, ENVIRONMENTALLY HAZARDOUS 1133 KLEBSTOFFE, UMWELTGEFÄHRDEND, Sondervorschrift 640D ADHESIVES (heptane), MARINE POLLUTANT ADHESIVES
---	--

· 14.3 Transport hazard class(es)

· ADR, IMDG



<ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>	3 Flammable liquids. 3
--	---------------------------

· IATA



<ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>	3 Flammable liquids. 3
--	---------------------------

· 14.4 Packing group

<ul style="list-style-type: none"> <li>· ADR, IMDG, IATA</li> </ul>	III
---	-----

· 14.5 Environmental hazards:

<ul style="list-style-type: none"> <li>· Marine pollutant:</li> <li>· Special marking (ADR):</li> </ul>	Product contains environmentally hazardous substances: heptane Yes Symbol (fish and tree) Symbol (fish and tree)
---	---

· 14.6 Special precautions for user

<ul style="list-style-type: none"> <li>· Danger code (Kemler):</li> <li>· EMS Number:</li> <li>· Stowage Category</li> </ul>	Warning: Flammable liquids. - F-E,S-D A
--	--

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

· Transport/Additional information:

<ul style="list-style-type: none"> <li>· ADR</li> <li>· Limited quantities (LQ)</li> <li>· Excepted quantities (EQ)</li> </ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
--	--

(Contd. on page 11)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 28

Revision: 26.06.2019

**Trade name: UHU KONTAKT Kraftkleber gel (Tube) < 350 g**

(Contd. of page 10)

· <b>Transport category</b>	3
· <b>Tunnel restriction code</b>	E
<hr style="border-top: 1px dashed black;"/>	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1133 ADHESIVES, 3, III, ENVIRONMENTALLY HAZARDOUS

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**  
E2 Hazardous to the Aquatic Environment  
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**
- **Please note:** Product for professional use!
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H361d Suspected of damaging the unborn child.  
H411 Toxic to aquatic life with long lasting effects.
- **Department issuing SDS:** UHU QESH

(Contd. on page 12)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 28

Revision: 26.06.2019

**Trade name: UHU KONTAKT Kraftkleber gel (Tube) < 350 g**

(Contd. of page 11)

· **Contact:** Dr. C. Hanf· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· **\* Data compared to the previous version altered.**

EU-EN