

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 13

Revision: 26.06.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
 - **Trade name: UHU greenit +150°C**
 - **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
 - **Application of the substance / the mixture** Adhesives
 - **1.3 Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
UHU GmbH & Co.KG
Herrmannstraße 7
D-77815 Bühl (Baden)
Tel.: 0049-(0)7223-284-0
email: sds@uhu.boltongroup.com
 - Fax: 0049-(0)7223-284-245
 - **Further information obtainable from:** UHU QESH
 - **1.4 Emergency telephone number:**
Tel.: + 49 (0) 30/19240 (Notruf)
Tel.: + 49 (0) 72 23/28 40
- England and Wales (NHS Direct) 111
Schottland (NHS 24) 111

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 13

Revision: 26.06.2019

Trade name: UHU greenit +150°C

(Contd. of page 1)

Hazard pictograms


GHS02 GHS07

Signal word Danger

Hazard-determining components of labelling:

 acetone
 ethyl acetate
 n-hexane

Hazard statements

 H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

 P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from open flames. - No smoking.
 P261 Avoid breathing vapours.
 P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P501 Dispose of contents/container in accordance with national regulations.

Additional information:

 EUH066 Repeated exposure may cause skin dryness or cracking.
 Contains Rosin. May produce an allergic reaction.



2.3 Other hazards
Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures
Description:

 Mixture of substances listed below with nonhazardous additions.
 Adhesive

Dangerous components:

CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-XXXX	acetone 	10-25%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-XXXX	ethyl acetate 	10-25%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 13

Revision: 26.06.2019

Trade name: UHU greenit +150°C

(Contd. of page 2)

CAS: 110-54-3 EINECS: 203-777-6	n-hexane ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	1-2.5%
CAS: 8050-09-7 EINECS: 232-475-7 Reg.nr.: 01-2119480418-32-xxxx	Rosin ⚠ Skin Sens. 1, H317	<1%
CAS: 68610-51-5 EINECS: 271-867-2	phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene ⚠ Repr. 2, H361d	<1%
CAS: 1314-13-2 EINECS: 215-222-5	zinc oxide ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	<1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** No special measures required.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 13

Revision: 26.06.2019

Trade name: UHU greenit +150°C

(Contd. of page 3)

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Send for recovery or disposal in suitable receptacles.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

67-64-1 acetone

IOELV (EU)	Long-term value: 1210 mg/m ³ , 500 ppm
AGW (Germany)	Long-term value: 1200 mg/m ³ , 500 ppm 2(I);AGS, DFG, EU, Y

141-78-6 ethyl acetate

IOELV (EU)	Short-term value: 1468 mg/m ³ , 400 ppm Long-term value: 734 mg/m ³ , 200 ppm
AGW (Germany)	Long-term value: 730 mg/m ³ , 200 ppm 2(I);DFG, EU, Y

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 13

Revision: 26.06.2019

Trade name: UHU greenit +150°C

(Contd. of page 4)

110-54-3 n-hexane

IOELV (EU)	Long-term value: 72 mg/m ³ , 20 ppm
AGW (Germany)	Long-term value: 180 mg/m ³ , 50 ppm 8(II);DFG, EU, Y

8050-09-7 Rosin

MAK (Germany)	vgl.Abschn.IV
---------------	---------------

· DNELs
67-64-1 acetone

Oral	Consumer DNEL, longterm oral	62 mg/kg bw/day
Dermal	Consumer DNEL, longterm dermal	62 mg/kg bw/day
Inhalative	Consumer DNEL, acute inhalation	mg/m ³ (rat)
	Consumer DNEL, longterm inhalation	mg/m ³ (rabbit) 200 mg/m ³

141-78-6 ethyl acetate

Oral	Consumer DNEL, chronic effect oral	4.5 mg/kg ()
Dermal	Consumer DNEL, chronic effect dermal	37 mg/kg ()
Inhalative	Consumer DNEL, acute inhalation	734 mg/m ³ ()
	Verbraucher, Chronische Wirkungen, Einatmen	367 mg/m ³ ()

8050-09-7 Rosin

Oral	Consumer DNEL, longterm oral	10 mg/kg bw/day (.)
Dermal	Consumer DNEL, longterm dermal	10 mg/kg bw/day (.)
Inhalative	Consumer DNEL, longterm inhalation	35 mg/m ³ (.)

· PNECs
67-64-1 acetone

PNEC Fresh water	10.6 mg/l
PNEC Marine water	1.06 mg/l
PNEC Soil	29.5 mg/kg

141-78-6 ethyl acetate

PNEC Fresh water	0.24 mg/l ()
PNEC Marine water	0.024 mg/l ()
PNEC Soil	0.148 mg/kg ()

8050-09-7 Rosin

PNEC Fresh water	0.0016 mg/l (.)
PNEC Marine water	0.0016 mg/l (.)

· Ingredients with biological limit values:
67-64-1 acetone

BGW (Germany)	80 mg/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Aceton
---------------	---

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 13

Revision: 26.06.2019

Trade name: UHU greenit +150°C

(Contd. of page 5)

110-54-3 n-hexane

BGW (Germany)	5 mg/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: 2.5-Hexandion plus 4.5-Dihydroxy-2-hexanon (nach Hydrolyse)
---------------	---

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
Not necessary if room is well-ventilated.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**
Solvent resistant gloves
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
glove material: butyl rubber
thickness of the glove material: 0,6 - 0,8 mm
breakthrough time (maximum wearing time): 60 - 120 min.
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**
Goggles recommended during refilling



Tightly sealed goggles

Goggles recommended during refilling

EU-EN

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 13

Revision: 26.06.2019

Trade name: UHU greenit +150°C

(Contd. of page 6)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Fluid
Colour:	Light yellow
· Odour:	Characteristic
· Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	55 °C

· Flash point: -17 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 460 °C

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower:	2.1 Vol %
Upper:	13 Vol %

· Vapour pressure at 20 °C: 233 hPa

· Density at 20 °C: 0.895 g/cm³

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic at 20 °C:	5100 mPas
Kinematic:	Not determined.

· Solvent content:

Organic solvents:	32.2 %
Water:	0.2 %
VOC (EC)	32.17 %

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 13

Revision: 26.06.2019

Trade name: UHU greenit +150°C

(Contd. of page 7)

- | | |
|------------------------------|---|
| Solids content: | 67.7 % |
| 9.2 Other information | All relevant physical data were determined for the mixture. All non determined data are not measurably or not relevant for the characterization of the mixture. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
------	------	------------------

141-78-6 ethyl acetate

Oral	LD50	5620 mg/kg (rabbit)
Inhalative	LC50/4 h	1600 mg/l (rat)

68610-51-5 phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene

Oral	LD50	16000 mg/kg (rat)
------	------	-------------------

1314-13-2 zinc oxide

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.

(Contd. on page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 13

Revision: 26.06.2019

Trade name: UHU greenit +150°C

(Contd. of page 8)

- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Harmful to aquatic organisms
Do not allow product to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

· European waste catalogue

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
-----------	--

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1133

(Contd. on page 10)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019


Version number 13

Revision: 26.06.2019

Trade name: UHU greenit +150°C

(Contd. of page 9)

<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG, IATA 	<p>1133 ADHESIVES 1133 KLEBSTOFFE, UMWELTGEFÄHRDEND, Sondervorschrift 640D ADHESIVES</p>
--	--

<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG, IATA 	<div style="text-align: center;">  </div> <ul style="list-style-type: none"> · Class · Label 	<p>3 Flammable liquids. 3</p>
--	---	-----------------------------------

<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 	<p>III</p>
---	------------

<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: 	<p>Yes</p>
--	------------

<ul style="list-style-type: none"> · 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category 	<p>Warning: Flammable liquids. - F-E,S-D A</p>
---	--

<ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code 	<p>Not applicable.</p>
--	------------------------

<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code 	<p>5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 E</p>
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	<p>5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p>

(Contd. on page 11)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 13

Revision: 26.06.2019

Trade name: UHU greenit +150°C

(Contd. of page 10)

· **UN "Model Regulation":** UN 1133 ADHESIVES, 3, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** UHU QESH

· **Contact:** Dr. C. Hanf

· **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 13

Revision: 26.06.2019

Trade name: UHU greenit +150°C

(Contd. of page 11)

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Repr. 2: Reproductive toxicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**

EU-EN