


Printing date 28.10.2015

Version number 15

Revision: 28.10.2015



- ENG



Printing date 28.10.2015

Version number 15

Revision: 28.10.2015

#### Trade name: UHU plus endfest 300 (Binder)

	(Contd. of page 1)		
P102	Keep out of reach of children.		
P103	Read label before use.		
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.		
P280	Wear protective gloves/protective clothing/eye protection/face protection.		
P273	Avoid release to the environment.		
P302+P352	IF ON SKIN: Wash with plenty of water.		
P305+P351+P3	38 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact		
	lenses, if present and easy to do. Continue rinsing.		
P501	Dispose of contents/container in accordance with local/regional/national/		
	international regulations.		
• Additional info	rmation:		
Contains epoxy	constituents. May produce an allergic reaction.		
<sup>•</sup> 2.3 Other hazar	2.3 Other hazards		
· Results of PBT	Results of PBT and vPvB assessment		
• PBT: Not applic	PBT: Not applicable.		
• vPvB: Not appli	cable.		

#### **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- · Description: Adhesive

· Dangerous components:				
CAS: 25068-38-6 NLP: 500-033-5 Reg.nr.: 01-2119456619-26-0002	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) � Aquatic Chronic 2, H411; � Skin Irrit. 2, H315;	70-100%		
CAS: 9003-36-5	Eye Irrit. 2, H319; Skin Sens. 1, H317 reaction product: bisphenol-F-(epichlorhydrin)	5.0-<10%		
Reg.nr.: 01-2119454392-40-0000	epoxy resin (number average molecular weight $\leq$ 700)	0,0 10,0		
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317			
• Additional information: For the wording of the listed risk phrases refer to section 16.				

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.

#### • After inhalation:

- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- Supply fresh air; consult doctor in case of complaints.
- After skin contact:
- If skin irritation continues, consult a doctor.
- Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After swallowing:
- Rinse out mouth and then drink plenty of water.
- Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)



Printing date 28.10.2015

Version number 15

Revision: 28.10.2015

Trade name: UHU plus endfest 300 (Binder)

(Contd. of page 2)

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

## **SECTION 5: Firefighting measures**

• **5.1 Extinguishing media** • **Suitable extinguishing agents:** Water spray

Carbon dioxide

Foam Fire-extinguishing powder

• **5.2 Special hazards arising from the substance or mixture** Formation of toxic gases is possible during heating or in case of fire. In case of fire, the following can be released: Carbon monoxide (CO) • **5.3 Advice for firefighters** 

· Protective equipment:

Do not inhale explosion gases or combustion gases. No special measures required.

## **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Send for recovery or disposal in suitable receptacles.

6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Store in cool, dry place in tightly closed receptacles. Prevent formation of aerosols.

· Information about fire - and explosion protection: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

- · Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Store receptacle in a well ventilated area.

Keep container tightly sealed.

- Storage class: 12
- · 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)



Printing date 28.10.2015

· Change in condition

· Flash point:


Melting point/Melting range:

Boiling point/Boiling range:

Version number 15

Revision: 28.10.2015

#### Trade name: UHU plus endfest 300 (Binder)



Undetermined. Undetermined.

Not applicable.

ENG -

(Contd. on page 5)



Printing date 28.10.2015

Version number 15

Revision: 28.10.2015

Trade name: UHU plus endfest 300 (Binder)

	(Contd. of page
· Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	1,15 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/w	ater): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	40000 s (DIN 53211/4)
Solvent content:	
Organic solvents:	0,0 %
VOC (EC)	0,00 %
Solids content:	91,0 %
9.2 Other information	No further relevant information available.

## SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• **10.3 Possibility of hazardous reactions** Exothermic polymerisation. Reacts with amines.

· 10.4 Conditions to avoid No further relevant information available.

- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity
- · Primary irritant effect:
- Skin corrosion/irritation Causes skin irritation.
- Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.

(Contd. on page 6)

<sup>-</sup> ENG



Printing date 28.10.2015

Version number 15

Revision: 28.10.2015

Trade name: UHU plus endfest 300 (Binder)

(Contd. of page 5)

- Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met. • **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

#### 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

#### · 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

## · European waste catalogue

08 04 09<sup>\*</sup> waste adhesives and sealants containing organic solvents or other dangerous substances

#### · Uncleaned packaging:

· Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

· 14.1 UN-Number	
ADR, IMDG, IATA	UN3082
	-
<sup>.</sup> 14.2 UN proper shipping name	
ADR	3082 ENVIRONMENTALLY HAZARDOU
	SUBSTANCE, LIQUID, N.O.S. (reaction produc bisphenol-A-(epichlorhydrin); epoxy resin (numbe



Printing date 28.10.2015

Version number 15

Revision: 28.10.2015

Trade name: UHU plus endfest 300 (Binder)

IMDG IATA	average molecular weight ≤ 700), reaction produ bisphenol-F-(epichlorhydrin) epoxy resin (numb average molecular weight ≤ 700)) 3082 UMWELTGEFÄHRDENDER STOF FLÜSSIG, N.A.G. (Reaktionsprodukt: Bisphenol- Epichlorhydrinharze mit durchschnittliche Molekulargewicht ≤ 700, Bisphenol- Epichlorhydrinharze MG < 700) ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (reaction produ bisphenol-A-(epichlorhydrin); epoxy resin (numb average molecular weight ≤ 700), reaction produ bisphenol-F-(epichlorhydrin) epoxy resin (numb average molecular weight ≤ 700), MARIN POLLUTANT ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (reaction produ bisphenol-A-(epichlorhydrin) epoxy resin (numb
	average molecular weight ≤ 700), reaction produces bisphenol-F-(epichlorhydrin) epoxy resin (numbes average molecular weight ≤ 700))
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	9 Miscellaneous dangerous substances ar articles. 9
14.4 Packing group ADR, IMDG, IATA	
ADR, INIDG, IATA	
14 5 Environmental hazarda	
<i>Marine pollutant: Special marking (ADR):</i>	Product contains environmentally hazardou substances: reaction product: bisphenol-, (epichlorhydrin); epoxy resin (number averag molecular weight ≤ 700) Yes Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
<i>Marine pollutant: Special marking (ADR): Special marking (IATA):</i>	Product contains environmentally hazardou substances: reaction product: bisphenol-, (epichlorhydrin); epoxy resin (number averag molecular weight ≤ 700) Yes Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree) Warning: Miscellaneous dangerous substance
Marine pollutant: Special marking (ADR): Special marking (IATA): 14.6 Special precautions for user Danger code (Kemler):	Product contains environmentally hazardou substances: reaction product: bisphenol-, (epichlorhydrin); epoxy resin (number averag molecular weight ≤ 700) Yes Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
Marine pollutant: Special marking (ADR): Special marking (IATA): 14.6 Special precautions for user Danger code (Kemler): EMS Number:	Product contains environmentally hazardou substances: reaction product: bisphenol-, (epichlorhydrin); epoxy resin (number averag molecular weight ≤ 700) Yes Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree) Warning: Miscellaneous dangerous substance and articles. 90 F-A,S-F
Marine pollutant: Special marking (ADR): Special marking (IATA): 14.6 Special precautions for user Danger code (Kemler): EMS Number: 14.7 Transport in bulk according to Ann of Marpol and the IBC Code	Product contains environmentally hazardou substances: reaction product: bisphenol-, (epichlorhydrin); epoxy resin (number averag molecular weight ≤ 700) Yes Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree) Warning: Miscellaneous dangerous substance and articles. 90 F-A,S-F
14.6 Special precautions for user Danger code (Kemler): EMS Number: 14.7 Transport in bulk according to Ani	Product contains environmentally hazardou substances: reaction product: bisphenol-, (epichlorhydrin); epoxy resin (number averag molecular weight ≤ 700) Yes Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree) Warning: Miscellaneous dangerous substance and articles. 90 F-A,S-F nex II Not applicable. Not dangerous according to the abov



Printing date 28.10.2015

Version number 15

Revision: 28.10.2015

Trade name: UHU plus endfest 300 (Binder)

	(Contd. of page 7)
· · Transport category · Tunnel restriction code	ml 3 E
<ul> <li>IMDG</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN); EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700), REACTION PRODUCT: BISPHENOL-F-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700)), 9, III, (E)

#### **SECTION 15: Regulatory information**

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Relevant phrases** H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.
- · Department issuing MSDS: CRD

#### Contact:

Frau A. Liar,

- Herr Dr. C. Hanf
- Abbreviations and acronyms:
- Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation, Hazard C Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment Chronic Hazard, Category 2
- \* \* Data compared to the previous version altered.

ENG —