

64511 - UHU EPOXY SCHNELLFEST BD 24ML*6 L204

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.05.2023

Version number 24 (replaces version 23)

Revision: 31.03.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name: UHU EPOXY SCHNELLFEST BD 24ML*6 L204

- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesive
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7
 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0
 E-mail: sds@boltonadhesives.com

Fax: 0049-(0)7223-284-245

• Further information obtainable from: UHU QESH

· 1.4 Emergency telephone number:

Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET) UHU products: + 49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @ https:// poisoncentres.echa.europa.eu/appointed-bodies

SECTION 2: Hazards identification

• 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

GHS07

Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



· Signal word Warning

(Contd. on page 2) EU-EN



Printing date 20.05.2023

Version number 24 (replaces version 23)

Revision: 31.03.2023

Trade name: UHU EPOXY SCHNELLFEST BD 24ML*6 L204

 Hazard-determining components of labelling: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight
reaction product: hisphonol A (onichlorhydrin) opeyy resin (number average melecular weight
reaction product. Displicitor-A-(epicition) and epoxy resin (number average molecular weight
700)
Hazard statements
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
Precautionary statements
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P261 Avoid breathing vapours.
P280 Wear protective gloves.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove conta lenses, if present and easy to do. Continue rinsing.
P501 Dispose of contents/container in accordance with national regulations.
Additional information:
EUH205 Contains epoxy constituents. May produce an allergic reaction.
2.3 Other hazards
Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive

· Dangerous components:

CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26-XXXX reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700) Aquatic Chronic 2, H411; \bigcirc Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Eye Irrit. 2; H319: C \geq 5% Skin Irrit. 2; H315: C \geq 5%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information: No special measures required.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. (Contd. on page 3)



Printing date 20.05.2023

Version number 24 (replaces version 23)

Revision: 31.03.2023

(Contd. of page 2)

Trade name: UHU EPOXY SCHNELLFEST BD 24ML*6 L204

· After swallowing: If symptoms persist consult doctor.

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions. • 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles.
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection: No special measures required.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Storage class: 10
- 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)



Printing date 20.05.2023

Version number 24 (replaces version 23)

Revision: 31.03.2023

Trade name: UHU EPOXY SCHNELLFEST BD 24ML*6 L204

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:
- The usual precautionary measures are to be adhered to when handling chemicals.
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.
- **Respiratory protection:** Not required.
- · Recommended filter device for short term use: Combination filter A-P1
- Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

Recommended thickness of the material: > 0,12 mm

Hand protection Material	: butyl-rubber (e.g. Butoject 898: material thickness 0,7 mm)
Break through time	: > 8 h

Material	: Ethyl Vinyl Alcohol Laminate (EVAL)
Break through time	: > 8 h

glove material for short-term use / splash: (10 min <BTT <480 min): nitrile rubber, neoprene rubber Nitrile rubber, NBR

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

(Contd. on page 5)



Printing date 20.05.2023

Version number 24 (replaces version 23)

Revision: 31.03.2023

(Contd. of page 4)

Trade name: UHU EPOXY SCHNELLFEST BD 24ML*6 L204

· Eye/face protection



L

Tightly sealed goggles

Goggles recommended during refilling

SECTION 9: Physical and chemical properties	
· 9.1 Information on basic physical and chem	ical properties
General Information	
Physical state	Fluid
· Colour:	Colourless
· Odour:	Amine-like
· Odour threshold:	Not determined.
 Melting point/freezing point: 	Undetermined.
Boiling point or initial boiling point and	
boiling range	Undetermined.
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
· Upper:	Not determined.
Flash point:	>150 °C
Decomposition temperature:	Not determined.
· pH at 20 °C	6
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	40000 mPas
Solubility	
· water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log	
value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	1.16 g/cm³
· Relative density	Not determined.
· Vapour density	Not determined.
• 9.2 Other information	All relevant physical data were determined for the
3.2 Other miorination	mixture. All non-determined data are not
	measurable or not relevant for the
	characterization of the mixture.
· Appearance:	
· Form:	Fluid
· Important information on protection of healt	
and environment, and on safety.	
· Auto-ignition temperature:	Product is not selfigniting.
• Explosive properties:	Product does not present an explosion hazard.
	(Contd. on page 6)

⁻ EU-EN



Printing date 20.05.2023

Version number 24 (replaces version 23)

Revision: 31.03.2023

Trade name: UHU EPOXY SCHNELLFEST BD 24ML*6 L204

	(C	ontd. of page
Solvent content:		
Solids content:	100.0 %	
· Molecular weight	700 g/mol	
Change in condition	Ū.	
Evaporation rate	Not determined.	
Information with regard to physical haz	ard	
classes		
· Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

 \cdot 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.

(Contd. on page 7) EU-EN



Printing date 20.05.2023

Version number 24 (replaces version 23)

Revision: 31.03.2023

(Contd. of page 6)

Trade name: UHU EPOXY SCHNELLFEST BD 24ML*6 L204

· Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

- [•] Recommendation
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Disposal must be made according to official regulations.

(Contd. on page 8)



Printing date 20.05.2023

Version number 24 (replaces version 23)

Revision: 31.03.2023

(Contd. of page 7)

Trade name: UHU EPOXY SCHNELLFEST BD 24ML*6 L204

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informa	tion
14.1 UN number or ID number ADR/ADN, IMDG, IATA	UN3082 -
14.2 UN proper shipping name ADR/ADN	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction produc bisphenol-A-(epichlorhydrin); epoxy resin (numbe
IMDG	average molecular weight ≤ 700)) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction produc bisphenol-A-(epichlorhydrin); epoxy resin (numbe average molecular weight ≤ 700)), MARINI POLLUTANT
ΙΑΤΑ	ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (reaction produc bisphenol-A-(epichlorhydrin); epoxy resin (numbe average molecular weight \leq 700))
14.3 Transport hazard class(es)	
ADR/ADN	
Class Label	9 (M6) Miscellaneous dangerous substances an articles. 9
IMDG, IATA	
Class	9 Miscellaneous dangerous substances an articles.
Label	9
14.4 Packing group ADR/ADN, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant: Special marking (ADR/ADN):	Symbol (fish and tree) Symbol (fish and tree)



Printing date 20.05.2023

Version number 24 (replaces version 23)

Revision: 31.03.2023

Trade name: UHU EPOXY SCHNELLFEST BD 24ML*6 L204

	(Contd. of page 8)
• Special marking (IATA):	Symbol (fish and tree)
 14.6 Special precautions for user 	Warning: Miscellaneous dangerous substances and articles.
 Hazard identification number (Kemler code): EMS Number: Stowage Category 	90 F-A,S-F A
 14.7 Maritime transport in bulk according to IMO instruments 	Not applicable.
· Transport/Additional information:	
 ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3
· Tunnel restriction code	(-)
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION P R O D U C T : B I S P H E N O L - A - (EPICHLORHYDRIN); EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700)), 9, III

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

• Named dangerous substances - ANNEX I None of the ingredients is listed.

- · Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 10) EU-EN



Printing date 20.05.2023

Version number 24 (replaces version 23)

Revision: 31.03.2023

Trade name: UHU EPOXY SCHNELLFEST BD 24ML*6 L204

· REGULATION (EU) 2019/1148

(Contd. of page 9)

 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H315 Causes skin irritation.

- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation Serious eye damage/irritation Skin sensitisation Hazardous to the aquatic environment - long- term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.	

· Department issuing SDS: UHU QESH

- · Contact: UHU QESH
- Date of previous version: 17.05.2022
- · Version number of previous version: 23
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society) PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

** Data compared to the previous version altered.

EU-EN -



64511 - UHU EPOXY SCHNELLFEST BD 24ML*6 L204

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.05.2023

Version number 19 (replaces version 18)

Revision: 31.03.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

· Trade name: UHU EPOXY SCHNELLFEST BD 24ML*6 L204

- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesive
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7
 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0

Fax: 0049-(0)7223-284-245

· Further information obtainable from: UHU QESH

· 1.4 Emergency telephone number:

E-mail: sds@boltonadhesives.com

Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET) UHU products: + 49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @ https:// poisoncentres.echa.europa.eu/appointed-bodies

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008

GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labelling:
- mercaptan polymer
- Hazard statements
- H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.

(Contd. on page 2)



Printing date 20.05.2023

Version number 19 (replaces version 18)

Revision: 31.03.2023

Trade name: UHU EPOXY SCHNELLFEST BD 24ML*6 L204

(Contd. of page 1)

P102 Keep out of reach of children.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of water.

P501 Dispose of contents/container in accordance with national regulations.

2.3 Other hazards

· Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

Dangerous components:		
CAS: 72244-98-5 EC number: 615-735-8 Reg.nr.: 01-2120118957-46- XXXX	mercaptan polymer	50-100%
CAS: 90-72-2 EINECS: 202-013-9 Index number: 603-069-00-0 Reg.nr.: 01-2119560597-27	2,4,6-tris(dimethylaminomethyl)phenol Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	≥2.5-<10%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- · General information: No special measures required.
- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.

(Contd. on page 3)



Printing date 20.05.2023

Version number 19 (replaces version 18)

Revision: 31.03.2023

(Contd. of page 2)

Trade name: UHU EPOXY SCHNELLFEST BD 24ML*6 L204

• 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• **7.1 Precautions for safe handling** No special precautions are necessary if used correctly. • **Information about fire - and explosion protection:** No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- Storage class: 10
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

- · Respiratory protection: Not required.
- Recommended filter device for short term use: Combination filter A-P1

(Contd. on page 4)



Printing date 20.05.2023

Version number 19 (replaces version 18)

Revision: 31.03.2023

Trade name: UHU EPOXY SCHNELLFEST BD 24ML*6 L204

	(Contd. of page 3)
· Hand protection	
Protective gloves	
The glove material has to be impermeable	le and resistant to the product/ the substance/ the
preparation.	
	tion of the penetration times, rates of diffusion and the
degradation Material of gloves	
Recommended thickness of the material: > 0	. 12 mm
	0 min <btt <480="" min):="" neoprene="" nitrile="" rubber,="" rubber<="" th=""></btt>
Nitrile rubber, NBR	
Penetration time of glove material	
	ow the penetration time has to be at least 10 minutes
(Permeation according to EN 374 Part 3: Lev Eye/face protection Goggles recommended	
Lyenace protection obggies recommended	
SECTION 9: Physical and chemical	properties
	· ·
9.1 Information on basic physical and che	mical properties
General Information Physical state	Fluid
Colour:	Colourless
Odour:	Amine-like
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and	
boiling range	Undetermined.
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined. Not determined.
Upper:	Nol delermined
Flach noint'	
	>100 °C
Decomposition temperature:	>100 °C Not determined.
Decomposition temperature: pH	>100 °C
Decomposition temperature: pH Viscosity:	>100 °C Not determined.
Decomposition temperature: pH Viscosity: Kinematic viscosity Dynamic at 20 °C:	>100 °C Not determined. Not determined.
Decomposition temperature: pH Viscosity: Kinematic viscosity Dynamic at 20 °C: Solubility	>100 °C Not determined. Not determined. 12500 mPas
· Dynamic at 20 °C: · Solubility · water:	>100 °C Not determined. Not determined.
Decomposition temperature: pH Viscosity: Kinematic viscosity Dynamic at 20 °C: Solubility water: Partition coefficient n-octanol/water (log	>100 °C Not determined. Not determined. 12500 mPas Not miscible or difficult to mix.
Decomposition temperature: pH Viscosity: Kinematic viscosity Dynamic at 20 °C: Solubility water: Partition coefficient n-octanol/water (log value)	>100 °C Not determined. Not determined. 12500 mPas Not miscible or difficult to mix. Not determined.
Decomposition temperature: pH Viscosity: Kinematic viscosity Dynamic at 20 °C: Solubility water: Partition coefficient n-octanol/water (log value) Vapour pressure:	>100 °C Not determined. Not determined. 12500 mPas Not miscible or difficult to mix.
Decomposition temperature: pH Viscosity: Kinematic viscosity Dynamic at 20 °C: Solubility water: Partition coefficient n-octanol/water (log value) Vapour pressure: Density and/or relative density	 >100 °C Not determined. Not determined. 12500 mPas Not miscible or difficult to mix. Not determined. Not determined.
Decomposition temperature: pH Viscosity: Kinematic viscosity Dynamic at 20 °C: Solubility water: Partition coefficient n-octanol/water (log value) Vapour pressure:	>100 °C Not determined. Not determined. 12500 mPas Not miscible or difficult to mix. Not determined.

- EU-EN



Printing date 20.05.2023

Version number 19 (replaces version 18)

Revision: 31.03.2023

Trade name: UHU EPOXY SCHNELLFEST BD 24ML*6 L204

	(Contd. of page
Vapour density	Not determined.
9.2 Other information	All relevant physical data were determined for the mixture. All non-determined data are no measurable or not relevant for the characterization of the mixture.
Appearance:	
Form:	Fluid
Important information on protection of hea	alth
and environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Solvent content:	
Solids content:	0.0 %
Change in condition	
Evaporation rate	Not determined.
Explosives Flammable gases	Void Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void Void
Flammable liquids	Void
Flammable solids Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	VOIG
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

• **10.4 Conditions to avoid** No further relevant information available.

 \cdot 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6) EU-EN



Printing date 20.05.2023

Version number 19 (replaces version 18)

Revision: 31.03.2023

(Contd. of page 5)

Trade name: UHU EPOXY SCHNELLFEST BD 24ML*6 L204

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity
- Not applicable.
- Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties
- None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

(Contd. on page 7)



Printing date 20.05.2023

Version number 19 (replaces version 18)

Revision: 31.03.2023

Trade name: UHU EPOXY SCHNELLFEST BD 24ML*6 L204

(Contd. of page 6)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information	
· 14.1 UN number or ID number · ADR/ADN, IMDG, IATA	not regulated
ADN	- not regulated
[·] 14.2 UN proper shipping name [·] ADR/ADN, ADN, IMDG, IATA	not regulated
 14.3 Transport hazard class(es) 	
· ADR/ADN, ADN, IMDG, IATA · Class	not regulated
· 14.4 Packing group · ADR/ADN, IMDG, IATA	not regulated
· 14.5 Environmental hazards:	Not applicable.
[·] 14.6 Special precautions for user	Not applicable.
 14.7 Maritime transport in bulk accordi IMO instruments 	i ng to Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
· UN "Model Regulation":	not regulated

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

 \cdot Named dangerous substances - ANNEX I None of the ingredients is listed.

• REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 8)

EU-EN



Printing date 20.05.2023

Version number 19 (replaces version 18)

Revision: 31.03.2023

Trade name: UHU EPOXY SCHNELLFEST BD 24ML*6 L204

· REGULATION (EU) 2019/1148

(Contd. of page 7)

 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

Hazardous to the aquatic environment - long- term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
Department incuring SDS: UULLOESU	

- Department issuing SDS: UHU QESH
- · Contact: UHU QESH
- · Date of previous version: 05.07.2021
- Version number of previous version: 18
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

- vPvB: very Persistent and very Bioaccumulative
- Acute Tox. 4: Acute toxicity Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

• * Data compared to the previous version altered.

EU-EN -