Fax: 0049-(0)7223-284-245



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2015 Version number 15 Revision: 28.10.2015

SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
- · Trade name: UHU plus endfest 300 Kartusche (Härter)
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

UHU GmbH & Co.KG Herrmannstraße 7 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0

email: info@uhu.boltongroup.de

· Further information obtainable from: CRD

• 1.4 Emergency telephone number: Tel.: +49 (0) 72 23/28 40

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eve Dam. 1 H318 Causes serious eye damage.



Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



P310



GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine

Triethylentetramin

Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

(Contd. on page 2)



Printing date 28.10.2015 Version number 15 Revision: 28.10.2015

Trade name: UHU plus endfest 300 Kartusche (Härter)

(Contd. of page 1)

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive

· Dangerous components:			
CAS: 10563-29-8	N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine	5,0-<10%	
EINECS: 234-148-4	Skin Corr. 1B, H314; Eye Dam. 1, H318;		
	Triethylentetramin	5,0-<10%	
EINECS: 203-950-6	Skin Corr. 1B, H314; Eye Dam. 1, H318; () Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412		

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Water spray

Carbon dioxide

Foam

Fire-extinguishing powder

Use fire extinguishing methods suitable to surrounding conditions.

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 3)



Printing date 28.10.2015 Version number 15 Revision: 28.10.2015

Trade name: UHU plus endfest 300 Kartusche (Härter)

(Contd. of page 2)

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

- · 5.3 Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.

No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Send for recovery or disposal in suitable receptacles.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Store in cool, dry place in tightly closed receptacles.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

- · Storage class: 8 A
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

112-24-3 Triethylentetramin

MAK (Germany) als Dampf und Aerosol;vgl.Abschn.IV

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

(Contd. on page 4)



Printing date 28.10.2015 Version number 15 Revision: 28.10.2015

Trade name: UHU plus endfest 300 Kartusche (Härter)

(Contd. of page 3)

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Avoid direct contact with the chemical/ the product/ the preparation by organisational measures.

- · Respiratory protection: Not necessary if room is well-ventilated.
- Protection of hands:

Protective gloves

Rubber gloves

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Not required.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical a	and chemical properties
· Appearance:	
Form:	Fluid
Colour:	Yellow
· Odour:	Amine-like
· Odour threshold:	Not determined.
· pH-value at 20 °C:	12 (1:1 in H2O)
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	278 °C
· Flash point:	135 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	0 ℃
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
	(Contd. on page 5)

— ENG



Printing date 28.10.2015 Version number 15 Revision: 28.10.2015

Trade name: UHU plus endfest 300 Kartusche (Härter)

		(Contd. of page 4)
· Density at 20 °C:	0,95 g/cm³	
· Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/w	ater): Not determined.	
· Viscosity:		
Dynamic at 20 °C:	32500 mPas	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	0,0 %	
VOC (EC)	0,00 %	
Solids content:	84,2 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

	, toute textent		
	· LD/LC50 values relevant for classification:		
	112-24-3 Triethylentetramin		
	Oral	LD50	2500 mg/kg (rat)
L	Dermal	LD50	805 mg/kg (rabbit)

- · Primary irritant effect:
- Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

ENG



Printing date 28.10.2015 Version number 15 Revision: 28.10.2015

Trade name: UHU plus endfest 300 Kartusche (Härter)

(Contd. of page 5)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system

Disposal must be made according to official regulations.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN2735
14.2 UN proper shipping name	
· ADR	2735 POLYAMINES, LIQUID, CORROSIVE,
	N.O.S. (N'-(3-aminopropyl)-N,N-dimethylpropane-
	1,3-diamine, TRIETHYLENETETRAMINE)
· IMDG, IATA	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (N'-
	(3-aminopropyl)-N,N-dimethylpropane-1,3-
	diamine, TRIETHYLENETETRAMINE)

- · 14.3 Transport hazard class(es)
- · ADR, IMDG, IATA



· Class 8 Corrosive substances.

· Label

(Contd. on page 7)



Printing date 28.10.2015 Version number 15 Revision: 28.10.2015

Trade name: UHU plus endfest 300 Kartusche (Härter)

	(Contd. of page
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number:	Warning: Corrosive substances. 80 F-A,S-B
Segregation groups	Alkalis
 14.7 Transport in bulk according to An of Marpol and the IBC Code 	nex II Not applicable.
Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 m 2 E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1 kg Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 m
UN "Model Regulation":	UN 2735 POLYAMINES, LIQUID, CORROSIVE N.O.S. (N'-(3-AMINOPROPYL)-N,N DIMETHYLPROPANE-1,3-DIAMINE TRIETHYLENETETRAMINE),8, II, (E)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

· Department issuing MSDS: CRD

(Contd. on page 8)



Revision: 28.10.2015 Printing date 28.10.2015 Version number 15

Trade name: UHU plus endfest 300 Kartusche (Härter)

(Contd. of page 7)

· Contact:

Frau A. Liar, Herr Dr. C. Hanf

· Abbreviations and acronyms:

Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

· * Data compared to the previous version altered.