

64641 - UHU MAX REPAIR POWER BS 8G L204

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.04.2023

Version number 40 (replaces version 39)

Revision: 12.04.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

• Trade name: UHU MAX REPAIR POWER BS 8G L204

• **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.

· Application of the substance / the mixture Adhesive

 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: Bison International Dr.A.F.Philipsstraat 9 NL-4462 EW Goes PO Box 160 NL-4460 AD Goes tel. +31 88 3235700

fax. +31 88 3235800 e mail: sds@boltonadhesives.com

· Further information obtainable from: Bison QESH

· 1.4 Emergency telephone number: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the CLP regulation.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- Signal word Void
- · Hazard statements Void
- · Additional information:
- EUH208 Contains trimethoxyvinylsilane. May produce an allergic reaction.
- Labelling of packages where the contents do not exceed 125 ml
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- 2.3 Other hazards During curing methanol (CAS 67-56-1) is produced.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Adhesive

· Dangerous components:

CAS: 13822-56-5	3-(trimethoxysilyl)propylamine	≥3-<10%
EINECS: 237-511-5	🚯 Eye Dam. 1, H318; 🚯 Skin Irrit. 2, H315	
Reg.nr.: 01-2119510159-45		
	(Co	ntd. on page 2)

EU-EN



Printing date 12.04.2023

Version number 40 (replaces version 39)

Revision: 12.04.2023

Trade name: UHU MAX REPAIR POWER BS 8G L204

	(Co	ntd. of page 1)
CAS: 78-08-0	triethoxy(vinyl)silane	2.5-10%
EINECS: 201-081-7	🔗 Flam. Liq. 3, H226	
CAS: 2768-02-7	trimethoxyvinylsilane	≥0.1-<1%
EINECS: 220-449-8	🛞 Flam. Liq. 2, H225; 🕦 Skin Sens. 1B, H317	
Index number: 014-049-00-0		
Reg.nr.: 01-2119513215-52		
· Additional information: For	the wording of the listed hazard phrases refer to section 16	3

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: No special measures required.
- After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- · 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Not required.

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

 \cdot 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

EU-EN

(Contd. on page 3)



Printing date 12.04.2023

Version number 40 (replaces version 39)

Revision: 12.04.2023

Trade name: UHU MAX REPAIR POWER BS 8G L204

(Contd. of page 2)

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling No special precautions are necessary if used correctly. • Information about fire - and explosion protection: No special measures required.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Storage class: 10
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
- The usual precautionary measures are to be adhered to when handling chemicals.
- Wash hands before breaks and at the end of work.
- · Respiratory protection: Not required.
- Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves Recommended thickness of the material: > 0,12 mm Nitrile rubber, NBR
- · Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· Eye/face protection Goggles recommended during refilling

SECTION 9: Physical and chemical properties

 9.1 Information on basic physica General Information 	al and chemical properties
 Physical state 	Fluid
· Colour:	Clear
· Odour:	Characteristic
· Odour threshold:	Not determined.

(Contd. on page 4)



Printing date 12.04.2023

Version number 40 (replaces version 39)

Revision: 12.04.2023

Trade name: UHU MAX REPAIR POWER BS 8G L204

	(Contd. of page
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and	
boiling range	194 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	102 °C
Ignition temperature:	400 °C
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	Not determined.
Kinematic viscosity	Not determined.
Dynamic at 20 °C:	10000 mPas
•	10000 1115 45
Solubility	Not missible or difficult to miss
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log	
value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	~1.11 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	All relevant physical data were determined for th mixture. All non-determined data are no measurable or not relevant for th characterization of the mixture.
Appearance:	
Form:	Fluid
Important information on protection of hea	lth
and environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Solvent content:	· · ·
Organic solvents:	0.0 %
Solids content:	47.5 %
Change in condition	
Evaporation rate	Not determined.
•	
Information with regard to physical haza	aru
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
 , , , ¹ , , ,	Void
Flammable solids	
Flammable solids Self-reactive substances and mixtures	Void
	Void Void
Self-reactive substances and mixtures	

www.uhu.com



Printing date 12.04.2023

Version number 40 (replaces version 39)

Revision: 12.04.2023

Trade name: UHU MAX REPAIR POWER BS 8G L204

		(Contd. of page 4)
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 • Acute toxicity Based on available data, the classification criteria are not met. · LD/LC50 values relevant for classification: 78-08-0 triethoxy(vinyl)silane Oral LD50 23000 mg/kg (rat) Dermal LD50 10000 mg/kg (rabbit) Skin corrosion/irritation Based on available data, the classification criteria are not met. · Serious eye damage/irritation Component CAS No. Method Species Conclusion BCOP OECD 437 3-Aminopropyl 13822-56-5 cattle, eye no ocular irritation trimethoxysilane • Respiratory or skin sensitisation Based on available data, the classification criteria are not met. · Germ cell mutagenicity Not applicable. Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. • **Reproductive toxicity** Based on available data, the classification criteria are not met. • STOT-single exposure Based on available data, the classification criteria are not met. • STOT-repeated exposure Based on available data, the classification criteria are not met. · Aspiration hazard Based on available data, the classification criteria are not met. Additional toxicological information: · Acute effects (acute toxicity, irritation and corrosivity) Not applicable. · Sensitisation Not applicable. · Repeated dose toxicity Not applicable.

(Contd. on page 6)

EU-EN



Printing date 12.04.2023

Version number 40 (replaces version 39)

Revision: 12.04.2023

(Contd. of page 5)

Trade name: UHU MAX REPAIR POWER BS 8G L204

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

Uncleaned packaging:

· Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN number or ID number		
ADR/ADN, IMDG, IATA	not regulated	
	-	
ADN	not regulated	
14.2 UN proper shipping name		
ADR/ADN, ADN, IMDG, IATA	not regulated	



Printing date 12.04.2023

Version number 40 (replaces version 39)

Revision: 12.04.2023

Trade name: UHU MAX REPAIR POWER BS 8G L204

	(Contd. of page 6
· 14.3 Transport hazard class(es)	
· ADR/ADN, ADN, IMDG, IATA · Class	not regulated
 14.4 Packing group ADR/ADN, IMDG, IATA 	not regulated
 14.5 Environmental hazards: Marine pollutant: 	Νο
· 14.6 Special precautions for user	Not applicable.
 14.7 Maritime transport in bulk accordi IMO instruments 	i ng to Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
· IMDG · Remarks:	Under certain conditions substances in Class 3 (flammable liquids) can be classified ir packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2
· UN "Model Regulation":	not regulated

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

- Named dangerous substances ANNEX I None of the ingredients is listed.
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

(Contd. on page 8)

EU-EN



Printing date 12.04.2023

Version number 40 (replaces version 39)

Revision: 12.04.2023

(Contd. of page 7)

Trade name: UHU MAX REPAIR POWER BS 8G L204

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- · Department issuing SDS: Bison QESH
- · Contact: Reach coordinator
- · Date of previous version: 07.04.2023
- Version number of previous version: 39
- Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Skin Sens. 1B: Skin sensitisation - Category 1B ** Data compared to the previous version altered.

EU-EN