

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 27

Revision: 26.06.2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

**1.1 Product identifier****Trade name:** UHU extra Alleskleber**1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

**Application of the substance / the mixture** Adhesives**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

UHU GmbH &amp; Co.KG

Herrmannstraße 7

D-77815 Bühl (Baden)

Tel.: 0049-(0)7223-284-0

email: sds@uhu.boltongroup.com

Fax: 0049-(0)7223-284-245

**Further information obtainable from:** UHU QESH**1.4 Emergency telephone number:**

Tel.: + 49 (0) 30/19240 (Notruf)

Tel.: + 49 (0) 72 23/28 40

England and Wales (NHS Direct) 111

Schottland (NHS 24) 111

### SECTION 2: Hazards identification

**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**

GHS02



GHS07

**Signal word** Danger

(Contd. on page 2)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 27

Revision: 26.06.2019

**Trade name: UHU extra Alleskleber**

(Contd. of page 1)

- **Hazard-determining components of labelling:**  
methyl acetate
- **Hazard statements**  
H225 Highly flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.
- **Precautionary statements**  
P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from open flames. - No smoking.  
P261 Avoid breathing vapours.  
P501 Dispose of contents/container in accordance with national regulations.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:**  
Mixture of substances listed below with nonhazardous additions.  
Adhesive

- **Dangerous components:**

CAS: 79-20-9 EINECS: 201-185-2 Reg.nr.: 01-2119459211-47-XXXX	methyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	25-50%
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43	ethanol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319	25-50%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** No special measures required.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.

(Contd. on page 3)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 27

Revision: 26.06.2019

**Trade name: UHU extra Alleskleber**

(Contd. of page 2)

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Send for recovery or disposal in suitable receptacles.  
Ensure adequate ventilation.  
Pick up mechanically.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep container tightly sealed.

(Contd. on page 4)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 27

Revision: 26.06.2019

**Trade name: UHU extra Alleskleber**

(Contd. of page 3)

- Store in cool, dry conditions in well sealed receptacles.
- **Storage class: 3**
- **7.3 Specific end use(s)** No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

##### · 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

##### **79-20-9 methyl acetate**

AGW (Germany)	Long-term value: 620 mg/m <sup>3</sup> , 200 ppm 2(I);DFG, AGS, Y
---------------	--

##### **64-17-5 ethanol**

AGW (Germany)	Long-term value: 380 mg/m <sup>3</sup> , 200 ppm 4(II);DFG, Y
---------------	--

- **DNELs**

##### **79-20-9 methyl acetate**

Oral	Consumer DNEL, longterm oral	44 mg/kg bw/day (.)
Dermal	Consumer DNEL, longterm dermal	44 mg/kg bw/day (.)
Inhalative	Consumer DNEL, longterm inhalation	131 mg/m <sup>3</sup> (.)

##### **64-17-5 ethanol**

Oral	Consumer DNEL, longterm oral	87 mg/kg bw/day (.)
Dermal	Consumer DNEL, longterm dermal	206 mg/kg bw/day (.)
Inhalative	Consumer DNEL, acute inhalation	950 mg/m <sup>3</sup> (.)
	Consumer DNEL, longterm inhalation	114 mg/m <sup>3</sup> (.)

- **PNECs**

##### **79-20-9 methyl acetate**

PNEC Fresh water	0.12 mg/l (.)
PNEC Marine water	0.012 mg/l (.)

##### **64-17-5 ethanol**

PNEC Fresh water	0.96 mg/l (.)
PNEC Marine water	0.79 mg/l (.)

- **Additional information:** The lists valid during the making were used as basis.

##### · 8.2 Exposure controls

- **Personal protective equipment:**

- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.

(Contd. on page 5)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 26.06.2019

Version number 27

Revision: 26.06.2019

**Trade name: UHU extra Alleskleber**

(Contd. of page 4)

- **Respiratory protection:**  
 Not necessary if room is well-ventilated.  
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**  
 Solvent resistant gloves  
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**  
 glove material: butyl rubber  
 thickness of the glove material: 0,6 - 0,8 mm  
 breakthrough time (maximum wearing time): 60 - 120 min.  
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
 The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**  
 Goggles recommended during refilling



Tightly sealed goggles

Goggles recommended during refilling

**SECTION 9: Physical and chemical properties**

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

<b>Form:</b>	Structurally viscous
<b>Colour:</b>	Colourless
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **pH-value:** Not determined.
- **Change in condition**

<b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	57 °C
- **Flash point:** -10 °C
- **Flammability (solid, gas):** Not applicable.

(Contd. on page 6)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 27

Revision: 26.06.2019

**Trade name: UHU extra Alleskleber**

(Contd. of page 5)

· <b>Ignition temperature:</b>	425 °C
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto-ignition temperature:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
Lower:	3.1 Vol %
Upper:	16 Vol %
· <b>Vapour pressure at 20 °C:</b>	220 hPa
· <b>Density at 20 °C:</b>	0.95 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
Dynamic at 20 °C:	90000 mPas
Kinematic:	Not determined.
· <b>Solvent content:</b>	
Organic solvents:	68.8 %
Water:	0.4 %
VOC (EC)	68.85 %
Solids content:	30.8 %
· <b>9.2 Other information</b>	All relevant physical data were determined for the mixture. All non determined data are not measurably or not relevant for the characterization of the mixture.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 7)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 27

Revision: 26.06.2019

**Trade name: UHU extra Alleskleber**

(Contd. of page 6)

- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

#### 79-20-9 methyl acetate

Oral	LD50	3705 mg/kg (rabbit)
------	------	---------------------

#### 64-17-5 ethanol

Oral	LD50	7060 mg/kg (rat)
------	------	------------------

Inhalative	LC50/4 h	20000 mg/l (rat)
------------	----------	------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow product to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

EU-EN

(Contd. on page 8)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 27

Revision: 26.06.2019

**Trade name: UHU extra Alleskleber**

(Contd. of page 7)

#### SECTION 13: Disposal considerations

**13.1 Waste treatment methods**
**Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

**European waste catalogue**

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
-----------	--

**Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

#### SECTION 14: Transport information

**14.1 UN-Number**
**ADR, IMDG, IATA**

UN1133

**14.2 UN proper shipping name**
**ADR**

1133 ADHESIVES

1133 KLEBSTOFFE, Sondervorschrift 640H

**IMDG, IATA**

ADHESIVES

**14.3 Transport hazard class(es)**
**ADR, IMDG, IATA**

**Class**

3 Flammable liquids.

**Label**

3

**14.4 Packing group**
**ADR, IMDG, IATA**

III

**14.5 Environmental hazards:**
**Marine pollutant:**

No

**14.6 Special precautions for user**

Warning: Flammable liquids.

**Danger code (Kemler):**

-

**EMS Number:**

F-E,S-D

**Stowage Category**

A

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 27

Revision: 26.06.2019

**Trade name: UHU extra Alleskleber**

(Contd. of page 8)

**· Transport/Additional information:**

**· ADR**

- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml
- **Transport category** 3
- **Tunnel restriction code** E

**· IMDG**

- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

- **UN "Model Regulation":** UN 1133 ADHESIVES, 3, III

**SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c** FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

· **Department issuing SDS:** UHU QESH

· **Contact:** Dr. C. Hanf

**· Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 10)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 26.06.2019

Version number 27

Revision: 26.06.2019

**Trade name: UHU extra Alleskleber**

(Contd. of page 9)

IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
DNEL: Derived No-Effect Level (REACH)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Liq. 2: Flammable liquids – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· \* **Data compared to the previous version altered.**

EU-EN