

Page 1/10

Fax: 0049-(0)7223-284-245

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019 Version

Version number 22 Revision: 26.06.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: UHU Alleskleber flinke flasche
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

UHU GmbH & Co.KG

Herrmannstraße 7

D-77815 Bühl (Baden)

Tel.:0049-(0)7223-284-0

email: sds@uhu.boltongroup.com

· Further information obtainable from: UHU QESH

· 1.4 Emergency telephone number:

Tel.: + 49 (0) 30/19240 (Notruf)

Tel.: + 49 (0) 72 23/28 40

England and Wales (NHS Direct) 111

Schottland (NHS 24) 111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

- 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

(Contd. on page 2)



Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019 Version number 22 Revision: 26.06.2019

Trade name: UHU Alleskleber flinke flasche

(Contd. of page 1)

· Hazard statements

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from open flames. - No smoking.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with national regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- Description:

Mixture of substances listed below with nonhazardous additions.

Adhesive

· Dangerous components:		
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43	ethanol Flam. Liq. 2, H225; UEye Irrit. 2, H319	25-50%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-XXXX	ethyl acetate Flam. Liq. 2, H225; UEye Irrit. 2, H319; STOT SE 3, H336	2.5-10%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-XXXX	acetone Flam. Liq. 2, H225;	2.5-10%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Do not induce vomiting; call for medical help immediately.
- $^{\cdot}$ 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)



Page 3/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019 Version number 22 Revision: 26.06.2019

Trade name: UHU Alleskleber flinke flasche

(Contd. of page 2)

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Send for recovery or disposal in suitable receptacles.

Ensure adequate ventilation.

Pick up mechanically.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Storage class: 3

(Contd. on page 4)





Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019 Version number 22 Revision: 26.06.2019

Trade name: UHU Alleskleber flinke flasche

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

Ingredien	ts with	limit values that require monitoring	at the workplace:
64-17-5 et	hanol		
AGW (Germany)		Long-term value: 380 mg/m³, 200 ppm 4(II);DFG, Y	
141-78-6	ethyl ac	cetate	
IOELV (El	J)	Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm	
AGW (Germany)		Long-term value: 730 mg/m³, 200 ppm 2(I);DFG, EU, Y	
67-64-1 ad	etone		
IOELV (El	J)	Long-term value: 1210 mg/m³, 500 ppm	
AGW (Germany)		Long-term value: 1200 mg/m³, 500 ppm 2(I);AGS, DFG, EU, Y	
DNELs			
64-17-5 et	hanol		
Oral	Consu	mer DNEL, longterm oral	87 mg/kg bw/day (.)
Dermal	Consu	mer DNEL, longterm dermal	206 mg/kg bw/day (.)
Inhalative	Consumer DNEL, acute inhalation		950 mg/m³ (.)
	Consu	mer DNEL, longterm inhalation	114 mg/m³ (.)
141-78-6	thyl ac	cetate	·
Oral	Consumer DNEL, chronic effect oral		4.5 mg/kg (_)
Dermal	Consumer DNEL, chronic effect dermal		37 mg/kg (_)
Inhalative	Consu	mer DNEL, acute inhalation	734 mg/m³ (_)
Verbraucher, Chronische Wirkungen,		ucher, Chronische Wirkungen, Einatm	en 367 kg/m³ (_)
67-64-1 ad			
Oral		mer DNEL, longterm oral	62 mg/kg bw/day
Dermal	Consu	mer DNEL, longterm dermal	62 mg/kg bw/day
Inhalative Consumer DNEL, a		mer DNEL, acute inhalation	mg/m³ (rat)
			mg/m³ (rabbit)
	Consu	mer DNEL, longterm inhalation	200 mg/m³
PNECs			





Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019 Version number 22 Revision: 26.06.2019

Trade name: UHU Alleskleber flinke flasche

		(Contd. of page 4)	
	PNEC Marine water	0.79 mg/l (.)	
	141-78-6 ethyl acetate		
	PNEC Fresh water	0.24 mg/l (_)	
	PNEC Marine water	0.024 mg/l (_)	
	PNEC Soil	0.148 mg/kg (_)	
	67-64-1 acetone		
	PNEC Fresh water	10.6 mg/l	
	PNEC Marine water	1.06 mg/l	
	PNEC Soil	29.5 mg/kg	
Ī	Ingredients with biological limit values:		
	67-64-1 acetone		
	BGW (Germany) 80 mg/l		
	Untersuchungsmaterial: Urin		
	Probennahmezeitpunkt: Expositionsende bzw. Schichtende		
	Parameter: Aceton		

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

glove material: butyl rubber

thickness of the glove material: 0,6 - 0,8 mm

breakthrough time (maximum wearing time): 60 - 120 min.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019 Version number 22 Revision: 26.06.2019

Trade name: UHU Alleskleber flinke flasche

(Contd. of page 5)

· Eye protection:

Goggles recommended during refilling



Tightly sealed goggles

Goggles recommended during refilling

9.1 Information on basic physical General Information	and chemical properties
Appearance:	
Form:	Fluid
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range: 55 °C	
Flash point:	-19 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	425 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	3.5 Vol %
Upper:	15 Vol %
Vapour pressure at 20 °C:	59 hPa
Density at 20 °C:	0.92305 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.





Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019 Version number 22 Revision: 26.06.2019

Trade name: UHU Alleskleber flinke flasche

	(Contd. of page 6
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 20 °C:	1400 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	58.7 %
Water:	8.0 %
VOC (EC)	58.69 %
Solids content:	25.1 %
· 9.2 Other information	All relevant physical data were determined for the mixture. All non determined data are not measurably on not relevant for the characterization of the mixture.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	· LD/LC50 values relevant for classification:		
64-17-5 et	64-17-5 ethanol		
Oral	LD50	7060 mg/kg (rat)	
Inhalative	LC50/4 h	20000 mg/l (rat)	
141-78-6	141-78-6 ethyl acetate		
Oral	LD50	5620 mg/kg (rabbit)	
Inhalative	LC50/4 h	1600 mg/l (rat)	
67-64-1 ad	67-64-1 acetone		
Oral	LD50	5800 mg/kg (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.

(Contd. on page 8)



Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019 Version number 22 Revision: 26.06.2019

Trade name: UHU Alleskleber flinke flasche

(Contd. of page 7)

- · Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow product to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

EU-EN

(Contd. on page 9)



Page 9/10

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 26.06.2019 Printing date 26.06.2019 Version number 22

Trade name: UHU Alleskleber flinke flasche

(Contd. of page 8)

SECTION 14: Transport information	
· 14.1 UN-Number · ADR, IMDG, IATA	UN1133
· 14.2 UN proper shipping name · ADR	1133 ADHESIVES 1133 KLEBSTOFFE, Sondervorschrift 640H
· IMDG, IATA	ADHESIVES
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):EMS Number:Stowage Category	- F-E,S-D A
· 14.7 Transport in bulk according to An of Marpol and the IBC Code	nex II Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
· Transport category · Tunnel restriction code	3 E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
	(Contd. on page

EU-EN



Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Version number 22 Revision: 26.06.2019 Printing date 26.06.2019

Trade name: UHU Alleskleber flinke flasche

(Contd. of page 9)

UN "Model Regulation": UN 1133 ADHESIVES, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: UHU QESH
- · Contact: Dr. C. Hanf
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

* Data compared to the previous version altered.

EU-EN