

Page 1/10

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 22

Revision: 26.06.2019

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

- Trade name: UHU Alleskleber Flex + Clean
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0 email: sds@uhu.boltongroup.com

• Further information obtainable from: UHU QESH • 1.4 Emergency telephone number: Tel.: + 49 (0) 30/19240 (Notruf)

Tel.: + 49 (0) 72 23/28 40

England and Wales (NHS Direct) 111 Schottland (NHS 24) 111

# **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



· Signal word Danger

Fax: 0049-(0)7223-284-245



Page 2/10

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 22

Revision: 26.06.2019

#### Trade name: UHU Alleskleber Flex + Clean

	(Contd. of page
· Hazard-determining components of labelling:	
methyl acetate	
acetone	
· Hazard statements	
H225 Highly flammable liquid and vapour.	
H336 May cause drowsiness or dizziness.	
· Precautionary statements	
P101 If medical advice is needed, have product container or label at hand.	
P102 Keep out of reach of children.	
P210 Keep away from open flames No smoking.	
P261 Avoid breathing vapours.	
P501 Dispose of contents/container in accordance with national regulations.	
2.3 Other hazards	
· Results of PBT and vPvB assessment	
· <b>PBT:</b> Not applicable.	
· vPvB: Not applicable.	

#### **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

#### Description:

Mixture of substances listed below with nonhazardous additions. Adhesive

· Dangerous components:		
CAS: 79-20-9 EINECS: 201-185-2 Reg.nr.: 01-2119459211-47-XXXX	methyl acetate ♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336	50-100%
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43	ethanol � Flam. Liq. 2, H225; � Eye Irrit. 2, H319	2.5-10%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-XXXX	acetone	2.5-10%
Additional information: For the wording of the listed hazard phrases refer to section 16.		

# **SECTION 4: First aid measures**

#### · 4.1 Description of first aid measures

· General information: No special measures required.

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly. • After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

• After swallowing: Do not induce vomiting; call for medical help immediately.

(Contd. on page 3)



Page 3/10

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 22

Revision: 26.06.2019

(Contd. of page 2)

#### Trade name: UHU Alleskleber Flex + Clean

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- Ensure adequate ventilation
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Send for recovery or disposal in suitable receptacles.
- Ensure adequate ventilation.
- Pick up mechanically.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- **Information about fire and explosion protection:** Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.

(Contd. on page 4)

EU-EN



Page 4/10

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 22

Revision: 26.06.2019

#### Trade name: UHU Alleskleber Flex + Clean

#### • Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

• Additional information about design of technical facilities: No further data; see item 7.

79-20-9 m	ethyl a	cetate		
AGW (Germany) Long-term value: 620 mg/m <sup>3</sup> , 200 ppm 2(I);DFG, AGS, Y				
64-17-5 et	hanol			
		Long-term value: 380 mg/m³, 2 4(II);DFG, Y	00 ppm	
67-64-1 ad	etone			
IOELV (El	J)	Long-term value: 1210 mg/m³,	500 ppm	
AGW (Germany) Long-term value: 1200 mg/m³, 500 ppm 2(I);AGS, DFG, EU, Y				
DNELs				
79-20-9 m	ethyl a	cetate		
Oral	Consumer DNEL, longterm oral		44 mg/kg bw/day (.)	
Dermal	Consumer DNEL, longterm dermal		44 mg/kg bw/day (.)	
Inhalative	nhalative Consumer DNEL, longterm inhalation		131 mg/m <sup>3</sup> (.)	
64-17-5 et	hanol			
Oral	Consumer DNEL, longterm oral		87 mg/kg bw/day (.)	
Dermal	Consumer DNEL, longterm dermal		206 mg/kg bw/day (.)	
Inhalative Consumer DNEL, acute inhalation		mer DNEL, acute inhalation	950 mg/m³ (.)	
	Consu	mer DNEL, longterm inhalation	114 mg/m³ (.)	
67-64-1 ad	cetone		1	
Oral	oral Consumer DNEL, longterm oral		62 mg/kg bw/day	
Dermal	Consumer DNEL, longterm dermal		62 mg/kg bw/day	
Inhalative Consumer DNEL, acute inhalation		mer DNEL, acute inhalation	mg/m³ (rat)	
			mg/m³ (rabbit)	
	Consu	mer DNEL, longterm inhalation	200 mg/m <sup>3</sup>	

(Contd. of page 3)



Page 5/10

- EU-EN -

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 22

Revision: 26.06.2019

### Trade name: UHU Alleskleber Flex + Clean

PNECs 79-20-9 methyl a	cotato
PNEC Fresh wate	
PNEC Marine wa	
64-17-5 ethanol	
PNEC Fresh wate	er 0.96 mg/l (.)
PNEC Marine wa	5 ()
67-64-1 acetone	
PNEC Fresh wate	er 10.6 mg/l
PNEC Marine wa	5
PNEC Maine wa	0
	29.5 mg/kg
-	biological limit values:
67-64-1 acetone	
BGW (Germany)	
	Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende
	Probennannezenpunkt. Expositionsende bzw. Schichtende
General protecti The usual precau Wash hands befo	<b>ve and hygienic measures:</b> tionary measures are to be adhered to when handling chemicals. re breaks and at the end of work.
The usual precau Wash hands befo Do not inhale gas <b>Respiratory prot</b> Not necessary if r	tive equipment: ve and hygienic measures: tionary measures are to be adhered to when handling chemicals. re breaks and at the end of work. es / fumes / aerosols. ection: oom is well-ventilated.
General protecti The usual precau Wash hands befo Do not inhale gas Respiratory prot Not necessary if r In case of brief ex exposure use self	<b>tive equipment:</b> <b>ve and hygienic measures:</b> tionary measures are to be adhered to when handling chemicals. re breaks and at the end of work. es / fumes / aerosols. <b>ection:</b> oom is well-ventilated. sposure or low pollution use respiratory filter device. In case of intensive or longer- contained respiratory protective device.
General protecti The usual precau Wash hands befo Do not inhale gas Respiratory prot Not necessary if r In case of brief ex exposure use self Protection of ha	tive equipment: ve and hygienic measures: tionary measures are to be adhered to when handling chemicals. re breaks and at the end of work. es / fumes / aerosols. ection: oom is well-ventilated. consure or low pollution use respiratory filter device. In case of intensive or longe- contained respiratory protective device. nds:
General protecti The usual precau Wash hands befo Do not inhale gas Respiratory prot Not necessary if r In case of brief ex exposure use self Protection of ha Solvent resistant Selection of the g	tive equipment: ve and hygienic measures: tionary measures are to be adhered to when handling chemicals. re breaks and at the end of work. es / fumes / aerosols. ection: oom is well-ventilated. consure or low pollution use respiratory filter device. In case of intensive or longe- contained respiratory protective device. nds:
General protecti The usual precau Wash hands befo Do not inhale gas Respiratory prot Not necessary if r In case of brief ex exposure use self Protection of ha Solvent resistant Selection of the g degradation	<b>tive equipment:</b> <b>ve and hygienic measures:</b> tionary measures are to be adhered to when handling chemicals. re breaks and at the end of work. es / fumes / aerosols. <b>ection:</b> oom is well-ventilated. consure or low pollution use respiratory filter device. In case of intensive or longe- contained respiratory protective device. <b>nds:</b> gloves love material on consideration of the penetration times, rates of diffusion and the
General protecti The usual precau Wash hands befo Do not inhale gas Respiratory prot Not necessary if r In case of brief exposure use self Protection of ha Solvent resistant Selection of the g degradation Material of glove	tive equipment: ve and hygienic measures: tionary measures are to be adhered to when handling chemicals. re breaks and at the end of work. es / fumes / aerosols. ection: oom is well-ventilated. toposure or low pollution use respiratory filter device. In case of intensive or longer- contained respiratory protective device. nds: gloves love material on consideration of the penetration times, rates of diffusion and the s
General protecti The usual precau Wash hands befo Do not inhale gas Respiratory prot Not necessary if r In case of brief ex- exposure use self Protection of ha Solvent resistant Selection of the g degradation Material of glove glove material: bu	<b>tive equipment:</b> <b>ve and hygienic measures:</b> tionary measures are to be adhered to when handling chemicals. re breaks and at the end of work. es / fumes / aerosols. <b>ection:</b> oom is well-ventilated. toposure or low pollution use respiratory filter device. In case of intensive or longer- contained respiratory protective device. <b>nds:</b> gloves love material on consideration of the penetration times, rates of diffusion and the <b>s</b> tyl rubber
General protecti The usual precau Wash hands befo Do not inhale gas Respiratory prot Not necessary if r In case of brief ex- exposure use self Protection of ha Solvent resistant Selection of the g degradation Material of glove glove material: but thickness of the g	<b>ive equipment:</b> <b>ve and hygienic measures:</b> tionary measures are to be adhered to when handling chemicals. re breaks and at the end of work. es / fumes / aerosols. <b>ection:</b> oom is well-ventilated. contained respiratory protective device. In case of intensive or longer- contained respiratory protective device. <b>nds:</b> gloves love material on consideration of the penetration times, rates of diffusion and the <b>s</b> tyl rubber love material: 0,6 - 0,8 mm
General protecti The usual precau Wash hands befo Do not inhale gas <b>Respiratory prot</b> Not necessary if r In case of brief ex exposure use self <b>Protection of ha</b> Solvent resistant Selection of the g degradation <b>Material of glove</b> glove material: but thickness of the g breakthrough time The selection of th of quality and var substances, the therefore to be ch	<pre>ive equipment: ve and hygienic measures: tionary measures are to be adhered to when handling chemicals. re breaks and at the end of work. es / fumes / aerosols. ection: oom is well-ventilated. posure or low pollution use respiratory filter device. In case of intensive or longe- contained respiratory protective device. nds: gloves love material on consideration of the penetration times, rates of diffusion and the s tyl rubber love material: 0,6 - 0,8 mm e (maximum wearing time): 60 - 120 min. ne suitable gloves does not only depend on the material, but also on further marking for manufacturer to manufacturer. As the product is a preparation of sever resistance of the glove material can not be calculated in advance and ha ecked prior to the application.</pre>
General protecti The usual precau Wash hands befo Do not inhale gas <b>Respiratory prot</b> Not necessary if r In case of brief ex- exposure use self <b>Protection of ha</b> Solvent resistant Selection of the g degradation <b>Material of glove</b> glove material: but thickness of the g breakthrough time The selection of the of quality and var substances, the therefore to be ch	<ul> <li>ive equipment:</li> <li>ve and hygienic measures:</li> <li>tionary measures are to be adhered to when handling chemicals.</li> <li>re breaks and at the end of work.</li> <li>es / fumes / aerosols.</li> <li>ection:</li> <li>oom is well-ventilated.</li> <li>cposure or low pollution use respiratory filter device. In case of intensive or longe-contained respiratory protective device.</li> <li>nds:</li> <li>gloves</li> <li>love material on consideration of the penetration times, rates of diffusion and the suitable gloves does not only depend on the material, but also on further markies from manufacturer to manufacturer. As the product is a preparation of sever resistance of the glove material can not be calculated in advance and ha ecked prior to the application.</li> <li>of glove material</li> </ul>



Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 22

Revision: 26.06.2019

(Contd. of page 5)

#### Trade name: UHU Alleskleber Flex + Clean

· Eye protection:

Goggles recommended during refilling

Tightly sealed goggles

Goggles recommended during refilling

9.1 Information on basic physical and chemical properties		
General Information		
Appearance:		
Form:	Fluid	
Colour:	Colourless	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range	: 55.8-56.6 °C	
Flash point: -13 °C		
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	425 °C	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product is not explosive. However, formation explosive air/vapour mixtures are possible.	
Explosion limits:		
Lower:	3.1 Vol %	
Upper:	16 Vol %	
Vapour pressure at 20 °C:	220 hPa	
Density at 20 °C:	0.98742 g/cm³	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	

EU-EN



Page 7/10

# Safety data sheet

# according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 22

Revision: 26.06.2019

#### Trade name: UHU Alleskleber Flex + Clean

	(Contd. of page 6
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 20 °C:	4400 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	65.9 %
Water:	0.4 %
VOC (EC)	65.85 %
Solids content:	33.8 %
• 9.2 Other information	All relevant physical data were determined for the mixture. All non determined data are not measurably or not relevant for the characterization of the mixture.

#### **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

• Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

79-20-9 r	nethyl ace	tate
Oral	LD50	3705 mg/kg (rabbit)

#### 64-17-5 ethanol

 Oral
 LD50
 7060 mg/kg (rat)

 Inhalative
 LC50/4 h
 20000 mg/l (rat)

# 67-64-1 acetone

- Oral LD50 5800 mg/kg (rat)
- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

(Contd. on page 8)

EU-EN



Page 8/10

# Safety data sheet

# according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 22

Revision: 26.06.2019

(Contd. of page 7)

#### Trade name: UHU Alleskleber Flex + Clean

- Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow product to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

#### **SECTION 13: Disposal considerations**

#### · 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

#### · European waste catalogue

08 04 09\* waste adhesives and sealants containing organic solvents or other hazardous substances

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

#### **SECTION 14: Transport information**

· 14.1 UN-Number

ADR, IMDG, IATA

UN1133

(Contd. on page 9)



Page 9/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 22

Revision: 26.06.2019

#### Trade name: UHU Alleskleber Flex + Clean

14.2 UN proper shipping name	
ADR	1133 ADHESIVES 1133 KLEBSTOFFE, Sondervorschrift 640H
· IMDG, IATA	ADHESIVES
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
· 14.4 Packing group · ADR, IMDG, IATA	III
<ul> <li>14.5 Environmental hazards:</li> <li>Marine pollutant:</li> </ul>	No
14.6 Special precautions for user Danger code (Kemler):	Warning: Flammable liquids. -
EMS Number: Stowage Category	F-E,S-D A
• 14.7 Transport in bulk according to An	
of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
<ul> <li>Transport category</li> <li>Tunnel restriction code</li> </ul>	3 E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
UN "Model Regulation":	UN 1133 ADHESIVES, 3, III

(Contd. on page 10)



Page 10/10

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 22

Revision: 26.06.2019

#### Trade name: UHU Alleskleber Flex + Clean

(Contd. of page 9)

#### **SECTION 15: Regulatory information**

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: UHU QESH
- · Contact: Dr. C. Hanf

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 \*\* Data compared to the previous version altered.

EU-EN