

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.06.2015

Version number 13

Revision: 19.06.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** UHU Alleskleber Flex + Clean
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Adhesives
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
UHU GmbH & Co.KG
Herrmannstraße 7
D-77815 Bühl (Baden)
Tel.:0049-(0)7223-284-0
email: info@uhu.boltongroup.de
- Fax: 0049-(0)7223-284-245
- **Further information obtainable from:** CRD
- **1.4 Emergency telephone number:** Tel.: +49 (0) 72 23/28 40

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02

- **Signal word** Danger
- **Hazard statements**
H225 Highly flammable liquid and vapour.
- **Precautionary statements**

P101	If medical advice is needed, have product container or label at hand.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

ENG

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.06.2015

Version number 13

Revision: 19.06.2015

Trade name: UHU Alleskleber Flex + Clean

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Adhesive

- **Dangerous components:**

CAS: 79-20-9 EINECS: 201-185-2 Reg.nr.: 01-2119459211-47-XXXX	methyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	50-80%
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43	ethanol ⚠ Flam. Liq. 2, H225	5,0-<10%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-XXXX 02-2119752542-40-0000	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	5,0-<10%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
 Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
 No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
 No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
 CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture**
 No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
 Ensure adequate ventilation
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Pick up mechanically.
 Send for recovery or disposal in suitable receptacles.
- **6.4 Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.06.2015

Version number 13

Revision: 19.06.2015

Trade name: UHU Alleskleber Flex + Clean

See Section 13 for disposal information.

(Contd. of page 2)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

Storage class: 3

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

79-20-9 methyl acetate

AGW (Germany)	Long-term value: 610 mg/m ³ , 200 ppm 4(II);DFG, Y
---------------	--

64-17-5 ethanol

AGW (Germany)	Long-term value: 960 mg/m ³ , 500 ppm 2(II);DFG, Y
---------------	--

67-64-1 acetone

IOELV (EU)	Long-term value: 1210 mg/m ³ , 500 ppm
AGW (Germany)	Long-term value: 1200 mg/m ³ , 500 ppm 2(I);Y, DFG, EU, AGS

Ingredients with biological limit values:

67-64-1 acetone

BGW (Germany)	80 mg/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Aceton
---------------	---

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.
Do not inhale gases / fumes / aerosols.

Avoid direct contact with the chemical/ the product/ the preparation by organisational measures.

Respiratory protection: Not required.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.06.2015

Version number 13

Revision: 19.06.2015

Trade name: UHU Alleskleber Flex + Clean

(Contd. of page 3)

- **Protection of hands:**
Solvent resistant gloves
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Not required.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Fluid
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C

· Flash point: -13 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 425 °C

· Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower:	3,1 Vol %
Upper:	16,0 Vol %

· Vapour pressure at 20 °C: 220 hPa

Density at 20 °C:	0,99 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.

· Solubility in / Miscibility with water:

Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic at 20 °C:	4400 mPas
Kinematic:	Not determined.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.06.2015

Version number 13

Revision: 19.06.2015

Trade name: UHU Alleskleber Flex + Clean

(Contd. of page 4)

· Solvent content:	
Organic solvents:	65,9 %
Water:	0,4 %
VOC (EC)	65,85 %

Solids content:	33,8 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

79-20-9 methyl acetate

Oral	LD50	3705 mg/kg (rabbit)
------	------	---------------------

64-17-5 ethanol

Oral	LD50	7060 mg/kg (rat)
Inhalative	LC50/4 h	20000 mg/l (rat)

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.06.2015

Version number 13

Revision: 19.06.2015

Trade name: UHU Alleskleber Flex + Clean

(Contd. of page 5)

- **Additional ecological information:**
- **General notes:**
*Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
 Do not allow product to reach ground water, water course or sewage system.*
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations


- **13.1 Waste treatment methods**
- **Recommendation**
*Must not be disposed together with household garbage. Do not allow product to reach sewage system.
 Disposal must be made according to official regulations.*

- **European waste catalogue**

08 04 09*	waste adhesives and sealants containing organic solvents or other dangerous substances
-----------	--

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|--|--|
| <ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG, IATA | UN1133 |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG, IATA | 1133 ADHESIVES, special provision 640H
1133 KLEBSTOFFE, Sondervorschrift 640H
ADHESIVES |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG, IATA | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | 3 Flammable liquids.
3 |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA | III |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: | No |
| <ul style="list-style-type: none"> · 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: | Warning: Flammable liquids.
33
F-E,S-D |
| <ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.06.2015

Version number 13

Revision: 19.06.2015

Trade name: UHU Alleskleber Flex + Clean

(Contd. of page 6)

· Transport/Additional information:
· ADR

- **Limited quantities (LQ)**
- **Excepted quantities (EQ)**

5L

Code: E1

 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

- **Transport category**
- **Tunnel restriction code**

3

D/E

· IMDG

- **Limited quantities (LQ)**
- **Excepted quantities (EQ)**

5L

Code: E1

 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN1133, ADHESIVES, special provision 640H, 3, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

· Department issuing MSDS: CRD
· Contact:

Frau A. Liar,
 Herr Dr. C. Hanf

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 2: Flammable liquids, Hazard Category 2

(Contd. on page 8)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 25.06.2015

Version number 13

Revision: 19.06.2015

Trade name: UHU Alleskleber Flex + Clean

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
· * **Data compared to the previous version altered.**

(Contd. of page 7)

ENG