

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023

Version number 8 (replaces version 7)

SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
- · Trade name: UHU HART KUNSTSTOFF 30g BL DE/FR/IT
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

UHU GmbH & Co.KG Herrmannstraße 7 D-77815 Bühl (Baden)

emaill: sds@boltonadhesives.com

Tel.:0049-(0)7223-284-0 Fax: 0049-(0)7223-284-245

· Further information obtainable from: UHU QESH

· 1.4 Emergency telephone number: Tel.: + 49 (0) 30/19240 (Notruf)

Tel.: + 49 (0) 72 23/28 40

England and Wales (NHS Direct) 111 Schottland (NHS 24) 111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling: acetone

(Contd. on page 2)

Revision: 06.05.2023

EU-EN

1/11 www.uhu.com



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023 Version number 8 (replaces version 7) Revision: 06.05.2023

Trade name: UHU HART KUNSTSTOFF 30g BL DE/FR/IT

(Contd. of page 1)

ethyl acetate

butanone

· Hazard statements

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P261 Avoid breathing vapours.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with national regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

· Determination of endocrine-disrupting properties

78-93-3 butanone

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49- XXXX	acetone State Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	25-50%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate Flam. Liq. 2, H225; Description Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	25-50%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43	butanone ♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-25%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 3)

List II

www.uhu.com 2/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023 Version number 8 (replaces version 7) Revision: 06.05.2023

Trade name: UHU HART KUNSTSTOFF 30g BL DE/FR/IT

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

EU-EN

www.uhu.com 3/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023 Version number 8 (replaces version 7) Revision: 06.05.2023

Trade name: UHU HART KUNSTSTOFF 30g BL DE/FR/IT

(Contd. of page 3)

EU-EN

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

	N 8: Exposure controls/person	ii piote	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
	ol parameters	- wina a - 4	Abo would be a
67-64-1 ac	ts with limit values that require moni	oring at	тпе workpiace:
	ng-term value: 1210 mg/m³, 500 ppm		
	ethyl acetate		
	nort-term value: 1468 mg/m³, 400 ppm		
	ng-term value: 734 mg/m³, 200 ppm		
78-93-3 b			
	ort-term value: 900 mg/m³, 300 ppm		
Lo	ng-term value: 600 mg/m³, 200 ppm		
DNELs			
67-64-1 ad	cetone		
Oral	Consumer, oral, longterm exposition	62 n	ng/kg bw/day
Dermal	Consumer, dermal, longterm expositio		ng/kg bw/day
Inhalative	tive Consumer, inhalation, longterm exposition 200 mg/m³		
	ethyl acetate	·	
Oral	Consumer, oral, longterm exposition		ng/kg bw/day
Dermal	Consumer, dermal, longterm exposition		ng/kg bw/day
Inhalative	Consumer DNEL, acute inhalation		mg/m³
	Consumer, inhalation, longterm exposi	ion 367	mg/m³
78-93-3 b			
Oral	Consumer, oral, longterm exposition		ng/kg bw/day
Dermal	Consumer, dermal, longterm exposition		mg/kg bw/day
Inhalative Consumer, inhalation, longterm exposition 106 mg/m³			
PNECs			
67-64-1 ad	cetone		
Fresh wat	S		
Marine water 1.06 mg/l			
Soil	29.5 mg/kg		

www.uhu.com 4/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023 Version number 8 (replaces version 7) Revision: 06.05.2023

Trade name: UHU HART KUNSTSTOFF 30g BL DE/FR/IT

(Contd. of page 4)

141-78-6 ethyl acetate			
Fresh water	0.26 mg/l		
Marine water	0.026 mg/l		
Soil	0.22 mg/kg		
78-93-3 butar	78-93-3 butanone		
Fresh water	55.8 mg/l		
Marine water	55.8 mg/l		
Soil	22.5 mg/kg		

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- · Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Recommended thickness of the material: > 0,12 mm

Nitrile rubber, NBR

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- Physical stateColour:Odour:FluidColourlessOharacteristic

(Contd. on page 6)

- EU-EN

www.uhu.com 5/11



Safety data sheet according to 1907/2006/EC, Article 31

Version number 8 (replaces version 7) Revision: 06.05.2023 Printing date 06.05.2023

Trade name: UHU HART KUNSTSTOFF 30g BL DE/FR/IT

(Contd. of page 5)

· Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

55.8-56.6 °C boiling range · Flammability Highly flammable.

· Lower and upper explosion limit

· Lower: 1.8 Vol % · Upper: 13 Vol % -19 °C · Flash point: 460 °C · Ignition temperature:

Decomposition temperature: Not determined. Not determined. · pH

· Viscosity:

· Kinematic viscosity Not determined. Dynamic at 20 °C: 2250 mPas

· Solubility

Not miscible or difficult to mix. · water:

Partition coefficient n-octanol/water (log

Not determined. value) · Vapour pressure at 20 °C: 233 hPa

Density and/or relative density

Density at 20 °C: 0.895 g/cm³ · Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information All relevant physical data were determined for the

mixture. All non-determined data are not measurable or not relevant for the

characterization of the mixture.

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety. · Auto-ignition temperature:

Product is not selfigniting. · Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

81.4 % · Organic solvents: · VOC (EC) 81.40 % · Solids content: 18.6 %

Change in condition

 Evaporation rate Not determined.

· Information with regard to physical hazard

classes

· Explosives Void · Flammable gases Void Void · Aerosols · Oxidising gases Void · Gases under pressure Void

· Flammable liquids Highly flammable liquid and vapour.

(Contd. on page 7)

EU-EN

6/11 www.uhu.com



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023 Version number 8 (replaces version 7) Revision: 06.05.2023

Trade name: UHU HART KUNSTSTOFF 30g BL DE/FR/IT

(Contd. of page 6)

		(Conta. or page
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
67-64-1 ad	67-64-1 acetone		
Oral	LD50	5800 mg/kg (rat)	
Dermal	LD50	20000 mg/kg (rabbit)	
141-78-6	141-78-6 ethyl acetate		
Oral	LD50	5620 mg/kg (rabbit)	
Inhalative	LC50/4 h	1600 mg/l (rat)	
78-93-3 butanone			
Oral	LD50	3300 mg/kg (rat)	
Dermal	LD50	5000 mg/kg (rabbit)	

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

(Contd. on page 8)

EU-EN

www.uhu.com 7/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023 Version number 8 (replaces version 7) Revision: 06.05.2023

Trade name: UHU HART KUNSTSTOFF 30g BL DE/FR/IT

(Contd. of page 7)

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

78-93-3 butanone

List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- **Uncleaned packaging:**
- · Recommendation: Disposal must be made according to official regulations.

FU-FN

(Contd. on page 9)

www.uhu.com 8/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023 Version number 8 (replaces version 7) Revision: 06.05.2023

Trade name: UHU HART KUNSTSTOFF 30g BL DE/FR/IT

(Contd. of page 8)

14.1 UN number or ID number ADR/ADN, IMDG, IATA	UN1133
14.2 UN proper shipping name ADR/ADN IMDG, IATA	1133 ADHESIVES ADHESIVES
14.3 Transport hazard class(es) ADR/ADN	
Class Label	3 (F1) Flammable liquids.
IMDG, IATA	
Class Label	3 Flammable liquids.
14.4 Packing group ADR/ADN, IMDG, IATA	III
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Hazard identification number (Kemler code):	
EMS Number: Stowage Category	F-E,S-D A
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information: Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
ADR/ADN Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 n Maximum net quantity per outer packaging: 10 ml
Transport category Tunnel restriction code	3 E

www.uhu.com 9/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023 Version number 8 (replaces version 7) Revision: 06.05.2023

Trade name: UHU HART KUNSTSTOFF 30g BL DE/FR/IT

(Contd. of page 9)

· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1133 ADHESIVES, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

67-64-1 acetone

Regulation (EC) No 273/2004 on drug precursors

67-64-1 a	acetone	3
78-93-3 k	butanone	3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

67-64-1	acetone	3
78-93-3	butanone	3

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

(Contd. on page 11)

EU-EN

www.uhu.com 10/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023 Version number 8 (replaces version 7) Revision: 06.05.2023

Trade name: UHU HART KUNSTSTOFF 30g BL DE/FR/IT

(Contd. of page 10)

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008		
Flammable liquids	Bridging principles	
	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.	

· Department issuing SDS: UHU QESH

· Contact: UHU QESH

· Date of previous version: 04.05.2021 · Version number of previous version: 7

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.

EU-EN

11/11 www.uhu.com