

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023

Version number 7 (replaces version 6)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: UHU PORZELLAN 30g BL DE/FR/IT
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

UHU GmbH & Co.KG Herrmannstraße 7

D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0

emaill: sds@boltonadhesives.com

· Further information obtainable from: UHU QESH

· 1.4 Emergency telephone number:

Tel.: + 49 (0) 30/19240 (Notruf) Tel.: + 49 (0) 72 23/28 40

England and Wales (NHS Direct) 111 Schottland (NHS 24) 111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- $\cdot \ \mbox{Hazard-determining components of labelling:}$

n-butyl acetate ethyl acetate

(Contd. on page 2)

Revision: 06.05.2023

Fax: 0049-(0)7223-284-245

- EU-EN

www.uhu.com 1/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023 Version number 7 (replaces version 6) Revision: 06.05.2023

Trade name: UHU PORZELLAN 30g BL DE/FR/IT

(Contd. of page 1)

· Hazard statements

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapours.

P501 Dispose of contents/container in accordance with national regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

r		
· Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate The Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	25-50%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide Carc. 2, H351, EUH212	10-25%
CAS: 9004-70-0 Index number: 603-037-01-3	nitrocellulose solutions, with not more than 12.6% nitrogen, by dry mass, and not more than 55% nitrocellulose Flam. Sol. 1, H228	10-25%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43	ethanol Flam. Liq. 2, H225; UEye Irrit. 2, H319	2.5-8%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate ♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	2.5-8%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 3)

www.uhu.com 2/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023 Version number 7 (replaces version 6) Revision: 06.05.2023

Trade name: UHU PORZELLAN 30g BL DE/FR/IT

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

EU-EN

www.uhu.com 3/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023 Version number 7 (replaces version 6) Revision: 06.05.2023

Trade name: UHU PORZELLAN 30g BL DE/FR/IT

(Contd. of page 3)

EU-EN

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

8.1 Contro	ol parameters			
	ts with limit values that require monitori	ng at the workplace:		
	n-butyl acetate			
	ort-term value: 723 mg/m³, 150 ppm ng-term value: 241 mg/m³, 50 ppm			
	ethyl acetate			
	nort-term value: 1468 mg/m³, 400 ppm ng-term value: 734 mg/m³, 200 ppm			
DNELs				
123-86-4 ו	n-butyl acetate			
Oral	Consumer, oral, longterm exposition	3.4 mg/kg bw/day		
Dermal	Consumer, dermal, longterm exposition	3.4 mg/kg bw/day		
Inhalative	Consumer, inhalation, longterm exposition	102.34 mg/m³		
64-17-5 et	hanol			
Oral	Consumer, oral, longterm exposition	87 mg/kg bw/day		
Dermal	Consumer, dermal, longterm exposition	343 mg/kg bw/day		
Inhalative	Consumer, inhalation, longterm exposition	950 mg/m³		
141-78-6	thyl acetate			
Oral	Consumer, oral, longterm exposition	4.5 mg/kg bw/day		
Dermal	Consumer, dermal, longterm exposition	37 mg/kg bw/day		
Inhalative	Consumer DNEL, acute inhalation	734 mg/m³		
	Consumer, inhalation, longterm exposition	367 mg/m³		
PNECs				
123-86-4 ı	n-butyl acetate			
Fresh water 0.18 mg/l				
Marine wa	ter 0.018 mg/l			
Soil	0.0903 mg/kg			
64-17-5 et	hanol			
Fresh wate	er 0.96 mg/l			
Marine wa	ter 0.79 mg/l			

www.uhu.com 4/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023 Version number 7 (replaces version 6) Revision: 06.05.2023

Trade name: UHU PORZELLAN 30g BL DE/FR/IT

(Contd. of page 4)

Soil	0.63 mg/kg
141-78-6 ethy	/l acetate
Fresh water	0.26 mg/l
Marine water	0.026 mg/l
Soil	0.22 mg/kg

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

- · Respiratory protection: Not required.
- · Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Recommended thickness of the material: > 0,12 mm

Nitrile rubber, NBR

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical stateColour:Odour:Characteristic

Odour threshold: Not determined.Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range 78 °C

· Flammability Highly flammable.

· Lower and upper explosion limit

• **Lower:** 1.2 Vol % • **Upper:** 15 Vol %

(Contd. on page 6)

EU-EN

www.uhu.com 5/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023 Version number 7 (replaces version 6) Revision: 06.05.2023

Trade name: UHU PORZELLAN 30g BL DE/FR/IT

(Contd. of page 5)

· Flash point: 12 °C · Ignition temperature: 180 °C

Decomposition temperature: Not determined.

· Viscosity:

Kinematic viscosity
 Dynamic at 20 °C:
 Not determined.
 14000 mPas

· Solubility

• water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log

value) Not determined. Vapour pressure at 20 °C: 58.7 hPa

Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

• **9.2 Other information** All relevant physical data were determined for the

mixture. All non-determined data are not measurable or not relevant for the

characterization of the mixture.

· Appearance:

· Form: Fluid

Important information on protection of health and environment, and on safety.

· **Auto-ignition temperature:** Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

Organic solvents: 59.7 %
 VOC (EC) 59.70 %
 Solids content: 40.3 %

· Change in condition

• Evaporation rate Not determined.

· Information with regard to physical hazard

classes

· Explosives Void

· Flammable gases Void

· Aerosols Void

· Oxidising gases Void

· Gases under pressure Void

• Flammable liquids Highly flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures, which emit

flammable gases in contact with water Void

· Oxidising liquids Void

(Contd. on page 7)

EU-EN

www.uhu.com 6/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023 Version number 7 (replaces version 6) Revision: 06.05.2023

Trade name: UHU PORZELLAN 30g BL DE/FR/IT

(Contd. of page 6)

· Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
 Desensitised explosives 	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
123-86-4 ו	123-86-4 n-butyl acetate		
Oral	LD50	13100 mg/kg (rat)	
Dermal	LD50	>5000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>21 mg/l (rat)	
13463-67-	7 titanium	n dioxide	
Oral	LD50	>20000 mg/kg (rat)	
Dermal	LD50	>10000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>6.82 mg/l (rat)	
64-17-5 et	64-17-5 ethanol		
Oral	LD50	7060 mg/kg (rat)	
Inhalative	LC50/4 h	20000 mg/l (rat)	
141-78-6 ethyl acetate			
Oral	LD50	5620 mg/kg (rabbit)	
Inhalative	LC50/4 h	1600 mg/l (rat)	
. Ckin corr	ooion/irrit	ation Based on available data, the classification criteria are not met	

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.

(Contd. on page 8)

EU-EN

www.uhu.com 7/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023 Version number 7 (replaces version 6) Revision: 06.05.2023

Trade name: UHU PORZELLAN 30g BL DE/FR/IT

(Contd. of page 7)

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR/ADN, IMDG, IATA UN1133

· 14.2 UN proper shipping name

ADR/ADN 1133 ADHESIVES

(Contd. on page 9)

- EU-EN

www.uhu.com 8/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023 Version number 7 (replaces version 6) Revision: 06.05.2023

Trade name: UHU PORZELLAN 30g BL DE/FR/IT

Class	IMDG, IATA	ADHESIVES
Class 3 (F1) Flammable liquids. 4 (F1) Flammable liquids. 4 (F1) Flammable liquids. 4 (F1) Flammable liquids. 4 (F2) Flammable liquids. 4 (F2) Flammable liquids. 5 (F2) Flammable liquids. 6 (F2) Flamm	14.3 Transport hazard class(es)	
Label 3 IMDG, IATA Class Label 3 14.4 Packing group ADR/ADN, IMDG, IATA 14.5 Environmental hazards: Not applicable. Warning: Flammable liquids. Hazard identification number (Kemler code): - EMS Number: F-E,S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Transport/Additional information: Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted Quantities (LQ) Except	ADR/ADN	
Label 3 IMDG, IATA Class Label 3 14.4 Packing group ADR/ADN, IMDG, IATA 14.5 Environmental hazards: Not applicable. Marning: Flammable liquids. Hazard identification number (Kemler code): F-E,S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Transport/Additional information: Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted Quantities (LQ)		
Label 3 IMDG, IATA Class Label 3 14.4 Packing group ADR/ADN, IMDG, IATA 14.5 Environmental hazards: Not applicable. Warning: Flammable liquids. Hazard identification number (Kemler code): - EMS Number: F-E,S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Transport/Additional information: Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted Quantities (LQ) Except	3	
Label 3 IMDG, IATA Class 3 Flammable liquids. 3 14.4 Packing group ADR/ADN, IMDG, IATA III 14.5 Environmental hazards: Not applicable. 14.6 Special precautions for user Hazard identification number (Kemler code): F-E,S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) 5L Excepted quantities (EQ) 5L Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) 5L Excepted quantities (LQ) 5L	Class	3 (F1) Flammable liquids.
Class Label 3 Flammable liquids. 14.4 Packing group ADR/ADN, IMDG, IATA III 14.5 Environmental hazards: Not applicable. 14.6 Special precautions for user Hazard identification number (Kemler code): - EMS Number: F-E,S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) 5L Excepted quantities (EQ) 5L Maximum net quantity per inner packaging: 30 r Maximum net quantity per outer packaging: 10 ml Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) 5L Excepted quantities (EQ) 5L	Label	
Label 3 14.4 Packing group ADR/ADN, IMDG, IATA III 14.5 Environmental hazards: Not applicable. 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: F-E,S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) 5L Excepted quantities (LQ) 5L Excepted quantities (LQ) 5L Code: E1	IMDG, IATA	
Label 3 14.4 Packing group ADR/ADN, IMDG, IATA III 14.5 Environmental hazards: Not applicable. 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: F-E,S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) 5L Excepted quantities (LQ) 5L Excepted quantities (LQ) 5L Code: E1		
ADR/ADN, IMDG, IATA 14.5 Environmental hazards: 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category 14.7 Maritime transport in bulk according to IMO instruments Transport/Additional information: Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (LQ) Excepted quantities (LQ) Limited quantities (LQ) Excepted Quantities (·
ADR/ADN, IMDG, IATA 14.5 Environmental hazards: 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category 14.7 Maritime transport in bulk according to IMO instruments Transport/Additional information: Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (LQ) Limited quantities (LQ) Excepted Quantities (14.4 Packing group	
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (LQ) Excepted quantities (LQ) Imulations SL Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 10 ml Transport category Tunnel restriction code E IMDG Limited quantities (LQ) Excepted quantities (EQ) SL Code: E1 Code: E1		III
Hazard identification number (Kemler code): - EMS Number: F-E,S-D Stowage Category A 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 10 ml Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) 5L Excepted Quantities (LQ) Code: E1	14.5 Environmental hazards:	Not applicable.
EMS Number: Stowage Category 14.7 Maritime transport in bulk according to IMO instruments Transport/Additional information: Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted Qua		
Stowage Category A		
14.7 Maritime transport in bulk according to IMO instruments Transport/Additional information: Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (LQ) Code: E1 Code: E1		
IMO instruments Transport/Additional information: Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (LQ) SL Maximum net quantity per inner packaging: 30 r Maximum net quantity per outer packaging: 10 ml Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) Excepted quantities (EQ) SL Code: E1 Code: E1 Code: E1 Code: E1 Code: E1 Code: E1		
Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (LQ) SL Code: E1 Maximum net quantity per inner packaging: 30 r Maximum net quantity per outer packaging: 10 ml Transport category 3 E IMDG Limited quantities (LQ) Excepted quantities (EQ) SL Code: E1		
On cargo aircraft only: 220 L ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (EQ) On cargo aircraft only: 220 L SL Code: E1 Maximum net quantity per inner packaging: 30 r Maximum net quantity per outer packaging: 10 ml E IMDG Limited quantities (LQ) Excepted quantities (EQ) SL Code: E1		
ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (LQ) Excepted quantities (LQ) Excepted quantities (EQ) 5L Maximum net quantity per inner packaging: 30 r Maximum net quantity per outer packaging: 10 ml Excepted quantities (LQ) 5L Code: E1	Quantity limitations	
Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (LQ) Excepted quantities (LQ) Excepted quantities (EQ) 5L Code: E1	ADDIADN	On cargo ancian only. 220 L
Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 r Maximum net quantity per outer packaging: 10 ml Transport category Tunnel restriction code E IMDG Limited quantities (LQ) Excepted quantities (EQ) Code: E1		51
Maximum net quantity per outer packaging: 10 ml Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1		* -
Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1		Maximum net quantity per inner packaging: 30 ml
Transport category Tunnel restriction code E IMDG Limited quantities (LQ) Excepted quantities (EQ) 5L Code: E1		
Tunnel restriction code E IMDG Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1	Transport category	
IMDG Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1		E
Excepted quantities (EQ) Code: E1	IMDG	
iviaximum net quantity per inner packaging: 30 r	Excepted quantities (EQ)	
Maximum net quantity per outer packaging: 10 ml		Maximum net quantity per outer packaging: 100

www.uhu.com 9/11

- EU-EN -



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023 Version number 7 (replaces version 6) Revision: 06.05.2023

Trade name: UHU PORZELLAN 30g BL DE/FR/IT

(Contd. of page 9)

UN "Model Regulation":

UN 1133 ADHESIVES, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H228 Flammable solid.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

(Contd. on page 11)

www.uhu.com 10/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2023 Version number 7 (replaces version 6) Revision: 06.05.2023

Trade name: UHU PORZELLAN 30g BL DE/FR/IT

(Contd. of page 10)

· Classification according to Regulation (EC) No 1272/2008		
Flammable liquids	Bridging principles	
	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.	

Department issuing SDS: UHU QESH

· Contact: UHU QESH

Date of previous version: 14.01.2022 · Version number of previous version: 6

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 2: Flammable liquids – Category 3 Flam. Sol. 1: Flammable solids – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

* Data compared to the previous version altered.

EU-EN

11/11 www.uhu.com