

7000438 - UHU FIRE PLACE SEALANT CQ 530G*12 L204

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.03.2023

Version number 33 (replaces version 32)

Revision: 15.03.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

· Trade name: UHU FIRE PLACE SEALANT CQ 530G*12 L204

- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Sealant
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: Bison International Dr.A.F.Philipsstraat 9 NL-4462 EW Goes PO Box 160 NL-4460 AD Goes tel. +31 88 3235700 fax. +31 88 3235800 e mail: sds@boltonadhesives.com

· Further information obtainable from: Bison QESH

· 1.4 Emergency telephone number: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008

GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



· Signal word Danger

- Hazard-determining components of labelling: Silicic acid, sodium salt
- Hazard statements
- H315 Causes skin irritation.
- H318 Causes serious eye damage.

(Contd. on page 2)



Printing date 15.03.2023

Version number 33 (replaces version 32)

Revision: 15.03.2023

Trade name: UHU FIRE PLACE SEALANT CQ 530G*12 L204

· Precautionary statements

(Contd. of page 1)

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P280 Wear eye protection / face protection.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310
 - Immediately call a POISON CENTER/doctor.
- · 2.3 Other hazards
- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Sealant

Dangerous components:

. .		
CAS: 1344-09-8	Silicic acid, sodium salt	10-25%
EINECS: 215-687-4	砂 Eye Dam. 1, H318; 🕔 Skin Irrit. 2, H315; STOT SE 3,	
Reg.nr.: 01-2119448725-31	H335	

Additional information:

The hazard of CAS No. 14808-60-7 is only applicable for respirable dust.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: No special measures required.
- · After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.

(Contd. on page 3) EU-EN



Printing date 15.03.2023

Version number 33 (replaces version 32)

Revision: 15.03.2023

Trade name: UHU FIRE PLACE SEALANT CQ 530G*12 L204

• 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
- Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

- Dispose contaminated material as waste according to item 13.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling No special precautions are necessary if used correctly. • Information about fire - and explosion protection: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 12
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:
- The usual precautionary measures are to be adhered to when handling chemicals.
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

(Contd. on page 4)

(Contd. of page 2)



Printing date 15.03.2023

Version number 33 (replaces version 32)

Revision: 15.03.2023

(Contd. of page 3)

Trade name: UHU FIRE PLACE SEALANT CQ 530G*12 L204

· Respiratory protection: Not required.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

Recommended thickness of the material: > 0,12 mm Nitrile rubber, NBR

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

• Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling **Body protection:** Use protective suit.

SECTION 9: Physical and chemical properties

Physical state	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point ar	nd
boiling range	100 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable.
Decomposition temperature:	Not determined.
pH at 20 °C	10
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to mix.



Printing date 15.03.2023

Version number 33 (replaces version 32)

Revision: 15.03.2023

Trade name: UHU FIRE PLACE SEALANT CQ 530G*12 L204

	(Contd. of pag	
· Partition coefficient n-octanol/water (log		
value)	Not determined.	
· Vapour pressure at 20 °C:	23 hPa	
• Density and/or relative density	1 000 1 000	
Density at 20 °C:	1.803-1.906 g/cm ³	
Relative density	Not determined.	
· Vapour density	Not determined.	
• 9.2 Other information	All relevant physical data were determined for the mixture. All non-determined data are n measurable or not relevant for the characterization of the mixture.	
Appearance:		
· Form:	Fluid	
 Important information on protection of heat 	lith	
and environment, and on safety.	Draduct is not colfigniting	
· Auto-ignition temperature:	Product is not selfigniting.	
• Explosive properties:	Product does not present an explosion hazard.	
· Solvent content:	28.0.0/	
· Water:	28.9 % 53.5 %	
· Solids content:	55.5 %	
 Change in condition Evaporation rate 	Not determined.	
	Not determined.	
· Information with regard to physical haza	ard	
classes		
· Explosives	Void	
· Flammable gases	Void	
· Aerosols	Void	
· Oxidising gases	Void	
[.] Gases under pressure	Void	
· Flammable liquids	Void	
· Flammable solids	Void	
Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
 Pyrophoric solids 	Void	
Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

(Contd. on page 6)



Printing date 15.03.2023

Version number 33 (replaces version 32)

Revision: 15.03.2023

(Contd. of page 5)

Trade name: UHU FIRE PLACE SEALANT CQ 530G*12 L204

· 10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

• **10.4 Conditions to avoid** No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation
- Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity

Not applicable.

- Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards
- Endocrine disrupting properties
- None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 7)



Printing date 15.03.2023

Version number 33 (replaces version 32)

Revision: 15.03.2023

(Contd. of page 6)

Trade name: UHU FIRE PLACE SEALANT CQ 530G*12 L204

12.7 Other adverse effects

· Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN number or ID number ADR/ADN, IMDG, IATA	not regulated
ADN	- not regulated
	notrogulated
14.2 UN proper shipping name ADR/ADN, ADN, IMDG, IATA	not regulated
14.3 Transport hazard class(es)	
ADR/ADN, ADN, IMDG, IATA Class	not regulated
14.4 Packing group ADR/ADN, IMDG, IATA	not regulated
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk accordi IMO instruments	ng to Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
IMDG	

EU-EN



Printing date 15.03.2023

Version number 33 (replaces version 32)

Revision: 15.03.2023

Trade name: UHU FIRE PLACE SEALANT CQ 530G*12 L204

	(Contd. of page 7)
· Remarks:	Under certain conditions substances in Class 3 (flammable liquids) can be classified in packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2
IN "Model Pequiation":	not regulated

UN "Model Regulation":

not regulated

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

- None of the ingredients is listed.
- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation

The classification of the mixture is generally based on the Serious eye damage/irritation calculation method using substance data according to Regulation (EC) No 1272/2008.

- · Department issuing SDS: Bison QESH
- Contact: Reach coordinator

(Contd. on page 9) EU-EN



Printing date 15.03.2023

Version number 33 (replaces version 32)

Revision: 15.03.2023

Trade name: UHU FIRE PLACE SEALANT CQ 530G*12 L204

	(Contd. of page 8)
 Date of previous version: 18.01.2022 	
Version number of previous version: 32	
Abbreviations and acronyms:	
ADR: Accord relatif au transport international des marchandises dangereuses par route (Europethe International Carriage of Dangerous Goods by Road)	ean Agreement Concerning
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
* Data compared to the previous version altered.	
	EU-EN -