

62991 - UHU PLUS MULTIFEST YE SY 50ML*6 DE

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.05.2023

Version number 14 (replaces version 13)

Revision: 06.05.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

• Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesive
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7
 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0
 E-mail: sds@boltonadhesives.com

Fax: 0049-(0)7223-284-245

· Further information obtainable from: UHU QESH

· 1.4 Emergency telephone number:

Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET) UHU products: + 49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @ https:// poisoncentres.echa.europa.eu/appointed-bodies

SECTION 2: Hazards identification · 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Lig. 2 H225 Highly flammable liquid and vapour. GHS05 corrosion Skin Corr. 1A H314 Causes severe skin burns and eye damage. Eve Dam. 1 H318 Causes serious eye damage. GHS07 Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation. · 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. (Contd. on page 2)

EU-EN



Printing date 20.05.2023

Version number 14 (replaces version 13)

Revision: 06.05.2023

Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

(Contd. of page 1) · Hazard pictograms GHS02 GHS05 GHS07 · Signal word Danger · Hazard-determining components of labelling: methyl methacrylate methacrylic acid Hazard statements H225 Highly flammable liquid and vapour. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. **Precautionary statements** P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P260 Do not breathe vapours. P280 Wear protective gloves. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P302+P352 IF ON SKIN: Wash with plenty of soap and water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501 Dispose of contents/container in accordance with national regulations. · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. · Determination of endocrine-disrupting properties 128-37-0 Butylated hydroxytoluene List II

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

CAS: 80-62-6	methyl methacrylate	50-100%
	Flam. Liq. 2, H225; (1) Skin Irrit. 2, H315; Skin	50-10070
Reg.nr.: 01-2119452498-28		
CAS: 79-41-4	methacrylic acid	≥5-≤10%
EINECS: 201-204-4	Skin Corr. 1A, H314; Acute Tox. 4, H302;	
Index number: 607-088-00-5		
	Specific concentration limit:	
	STOT SE 3; H335: C ≥1 %	
		(Contd. on page



Printing date 20.05.2023

Version number 14 (replaces version 13)

Revision: 06.05.2023

Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

		(Contd. of page 2)
CAS: 128-37-0	Butylated hydroxytoluene	≥0.025-<0.25%
EINECS: 204-881-4	Aquatic Acute 1, H400; Aquatic Chronic 1,	
	H410; 🕧 Acute Tox. 4, H302	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
- Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to item 13.

- Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Printing date 20.05.2023

Version number 14 (replaces version 13)

Revision: 06.05.2023

Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- Information about fire and explosion protection:
 Keep ignition sources away Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate

IOELV Short-term value: 100 ppm

Long-term value: 50 ppm

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
- The usual precautionary measures are to be adhered to when handling chemicals.
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.
- · Respiratory protection: Not required.
- Hand protection



Protective gloves

(Contd. on page 5)

(Contd. of page 3)

EU-EN



Printing date 20.05.2023

Version number 14 (replaces version 13)

Revision: 06.05.2023

Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

(Contd. of page 4) The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

Recommended thickness of the material: > 0,12 mm

- Nitrile rubber, NBR
- Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

SECTION 9: Physical and chemi	p	
9.1 Information on basic physical and	chemical properties	
General Information		
Physical state	Fluid	
Colour:	Whitish	
Odour:	Pungent	
Odour threshold:	Not determined.	
Melting point/freezing point:	Undetermined.	
Boiling point or initial boiling point and	d	
boiling range	101 °C	
Flammability	Highly flammable.	
Lower and upper explosion limit		
Lower:	2.1 Vol %	
Upper:	12.5 Vol %	
Flash point:	10 °C	
Ignition temperature:	430 °C	
Decomposition temperature:	Not determined.	
pH at 20 °C	3.5	
Viscosity:		
Kinematic viscosity	Not determined.	
Dynamic at 20 °C:	48000 mPas	
Solubility		
water:	Not miscible or difficult to mix.	
Partition coefficient n-octanol/water (lo	bg	
value)	Not determined.	
Vapour pressure at 20 °C:	47 hPa	
Density and/or relative density		
Density at 20 °C:	0.951 g/cm³	
Relative density	Not determined.	



Printing date 20.05.2023

Version number 14 (replaces version 13)

Revision: 06.05.2023

Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

	(Contd. of page s
Vapour density	Not determined.
9.2 Other information	All relevant physical data were determined for the mixture. All non-determined data are no measurable or not relevant for the characterization of the mixture.
Appearance:	
Form:	Pasty
Important information on protection of hea	alth
and environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation o
	explosive air/vapour mixtures are possible.
Solvent content:	
Solids content:	30.0 %
Change in condition	
Evaporation rate	Not determined.
classes Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
Substances and mixtures, which emit flammable gases in contact with water	Void
flammable gases in contact with water	Void Void
flammable gases in contact with water Oxidising liquids Oxidising solids	
flammable gases in contact with water Oxidising liquids Oxidising solids Organic peroxides	Void Void Void
flammable gases in contact with water Oxidising liquids	Void Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 7)

EU-EN



Printing date 20.05.2023

Version number 14 (replaces version 13)

Revision: 06.05.2023

(Contd. of page 6)

Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

• **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

 $^{\cdot}$ 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

- · LD/LC50 values relevant for classification:
- 80-62-6 methyl methacrylate

Oral LD50 7872 mg/kg (rat)

79-41-4 methacrylic acid

Oral LD50 1332 mg/kg (mouse) Dermal LD50 500 mg/kg (rabbit)

128-37-0 Butylated hydroxytoluene

Oral LD50 890 mg/kg (rat)

· Skin corrosion/irritation

Causes severe skin burns and eye damage.

- · Serious eye damage/irritation
- Causes serious eye damage.

· Respiratory or skin sensitisation May cause an allergic skin reaction.

- · Germ cell mutagenicity
- Not applicable.

Based on available data, the classification criteria are not met.

- Carcinogenicity Based on available data, the classification criteria are not met.
- \cdot Reproductive toxicity Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards

· Endocrine disrupting properties

128-37-0 Butylated hydroxytoluene

List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 8)



Printing date 20.05.2023

Version number 14 (replaces version 13)

Revision: 06.05.2023

(Contd. of page 7)

Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

· 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

· 12.7 Other adverse effects

· Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

· 14.1 UN number or ID number · ADR/ADN, IMDG, IATA	UN2924
 14.2 UN proper shipping name ADR/ADN IMDG, IATA 	2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S (METHYL METHACRYLATE MONOMEF STABILIZED, METHACRYLIC ACIE STABILIZED) FLAMMABLE LIQUID, CORROSIVE, N.O.S (METHYL METHACRYLATE MONOMEF STABILIZED, METHACRYLIC ACIE STABILIZED)
• 14.3 Transport hazard class(es) • ADR/ADN • Class	3 (FC) Flammable liquids.
· Label	3+8



Printing date 20.05.2023

Version number 14 (replaces version 13)

Revision: 06.05.2023

Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

	(Contd. of page
· IMDG	
· Class · Label	3 Flammable liquids. 3/8
·IATA	
· Class · Label	3 Flammable liquids. 3 (8)
· 14.4 Packing group · ADR/ADN, IMDG, IATA	
· 14.5 Environmental hazards:	Not applicable.
 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Segregation groups Stowage Category Stowage Code 	Warning: Flammable liquids. 338 F-E,S-C (SGG1) Acids B SW2 Clear of living quarters.
 14.7 Maritime transport in bulk according to IMO instruments 	Not applicable.
 Transport/Additional information: Quantity limitations 	On passenger aircraft/rail: 1 L On cargo aircraft only: 5 L
 ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) 	1L Code: E2 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 50 ml
 Transport category Tunnel restriction code 	2 D/E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	1L Code: E2 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 50 ml
· UN "Model Regulation":	UN 2924 FLAMMABLE LIQUID, CORROSIV N.O.S. (METHYL METHACRYLATE MONOME STABILIZED, METHACRYLIC ACID,
	(Contd. on page



.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.05.2023

Version number 14 (replaces version 13)

Revision: 06.05.2023

Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

(Contd. of page 9)

STABILIZED), 3 (8), II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II
- None of the ingredients is listed.
- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors
- None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 11)



Printing date 20.05.2023

Version number 14 (replaces version 13)

Revision: 06.05.2023

Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

	Bridging principles
Skin corrosion/irritation Serious eye damage/irritation Skin sensitisation Specific target organ toxicity (single exposu	The classification of the mixture is generally base on the calculation method using substance dat according to Regulation (EC) No 1272/2008. (Ire)
 Department issuing SDS: UHU QESH Contact: UHU QESH Date of previous version: 12.02.2022 Version number of previous version: 13 Abbreviations and acronyms: ADR: Accord relatif au transport international des mathe International Carriage of Dangerous Goods by Roa IMDG: International Maritime Code for Dangerous Good IATA: International Air Transport Association GHS: Globally Harmonised System of Classification ar EINECS: European Inventory of Existing Commercial CAS: Chemical Abstracts Service (division of the Ame LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent 	ods nd Labelling of Chemicals Chemical Substances ces



62991 - UHU PLUS MULTIFEST YE SY 50ML*6 DE

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.05.2023

Version number 15 (replaces version 14)

Revision: 06.05.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesive
- **1.3 Details of the supplier of the safety data sheet** • **Manufacturer/Supplier:** UHU GmbH & Co.KG Herrmannstraße 7 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0 E-mail: sds@boltonadhesives.com

Fax: 0049-(0)7223-284-245

• Further information obtainable from: UHU QESH

· 1.4 Emergency telephone number:

Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET) UHU products: + 49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @ https:// poisoncentres.echa.europa.eu/appointed-bodies

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



· Signal word Danger

(Contd. on page 2) EU-EN



Printing date 20.05.2023

Version number 15 (replaces version 14)

Revision: 06.05.2023

Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

Hazard	determining components of labelling:	(Contd. of page
	ethacrylate	
	statements	
H225 Hig	hly flammable liquid and vapour.	
	uses skin irritation.	
H317 Ma	y cause an allergic skin reaction.	
H335 Ma	y cause respiratory irritation.	
	onary statements	
P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P261	Avoid breathing vapours.	
	Wear protective gloves.	
P302+P3	52 IF ON SKIN: Wash with plenty of soap and water.	
P501	Dispose of contents/container in accordance with national regulations.	
2.3 Othe	r hazards	
Results	of PBT and vPvB assessment	
PBT: No	t applicable.	
vPvB: N	ot applicable.	

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive

 Dangerous components: 		
CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6 Reg.nr.: 01-2119452498-28	methyl methacrylate	50-100%
CAS: 34562-31-7 EINECS: 252-091-3 Reg.nr.: 01-2120769712-47	3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319	≥2.5-<10%
CAS: 128-37-0 EINECS: 204-881-4 Reg.nr.: 01-2119565113-46 01-2119555270-46	Butylated hydroxytoluene Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.025-<0.25%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

EU-EN



Printing date 20.05.2023

Version number 15 (replaces version 14)

Revision: 06.05.2023

(Contd. of page 2)

Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Storage class: 3

(Contd. on page 4)



Printing date 20.05.2023

Version number 15 (replaces version 14)

Revision: 06.05.2023

(Contd. of page 3)

Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate

IOELV Short-term value: 100 ppm

Long-term value: 50 ppm

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:
- The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- **Respiratory protection:** Not required.
- Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Recommended thickness of the material: > 0,12 mm Nitrile rubber, NBR

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

(Contd. on page 5)

EU-EN



Printing date 20.05.2023

Version number 15 (replaces version 14)

Revision: 06.05.2023

Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

(Contd. of page 4)

9.1 Information on basic physical and ch	emical properties
General Information	
Physical state	Fluid
Colour:	Yellow
Odour:	Pungent
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and	Shacterninea.
boiling range	101 °C
Flammability	Highly flammable.
Lower and upper explosion limit	
	2.1 Vol %
Lower:	
Upper:	12.5 Vol %
Flash point:	10 °C
Ignition temperature:	430 °C
Decomposition temperature:	Not determined.
pH at 20 °C	5.5
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic at 20 °C:	0.6 mPas
Solubility	
water at 20 °C:	1.6 g/l
Partition coefficient n-octanol/water (log	-
value)	Not determined.
Vapour pressure at 20 °C:	47 hPa
Density and/or relative density	
Density at 20 °C:	0.94 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	All relevant physical data were determined for th
	mixture. All non-determined data are no
	measurable or not relevant for th
	characterization of the mixture.
Appearance:	D .
Form:	Pasty
Important information on protection of he	ealth
and environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation
	explosive air/vapour mixtures are possible.
Solvent content:	
Solids content:	2.0 %
Change in condition	
Evaporation rate	Not determined.
•	
Information with regard to physical ha	zaro
classes Explosives	
	Void



Printing date 20.05.2023

Version number 15 (replaces version 14)

Revision: 06.05.2023

Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

	(Contd. of page 5
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION	11:	Toxicologic	al inforr	nation
---------	-----	-------------	-----------	--------

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008** • **Acute toxicity** Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

80-62-6 methyl methacrylate

- Oral LD50 7872 mg/kg (rat)
- 128-37-0 Butylated hydroxytoluene
- Oral LD50 890 mg/kg (rat)

· Skin corrosion/irritation

- Causes skin irritation.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- Germ cell mutagenicity
- Not applicable.
- Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)



Printing date 20.05.2023

Version number 15 (replaces version 14)

Revision: 06.05.2023

Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

(Contd. of page 6)

· STOT-single exposure May cause respiratory irritation.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards

• Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number
 ADR/ADN, IMDG, IATA

UN1133

(Contd. on page 8)



Printing date 20.05.2023

Version number 15 (replaces version 14)

Revision: 06.05.2023

Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

	(Contd. of page
· 14.2 UN proper shipping name · ADR/ADN	1133 ADHESIVES solution, special provisio 640D ADHESIVES solution
	ADRESIVES Solution
· 14.3 Transport hazard class(es) · ADR/ADN	
· Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR/ADN, IMDG, IATA	II
[·] 14.5 Environmental hazards:	Not applicable.
 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category Stowage Code 	Warning: Flammable liquids. 33 F-E,S-D C SW1 Protected from sources of heat. SW2 Clear of living quarters.
 14.7 Maritime transport in bulk according to IMO instruments 	Not applicable.
 Transport/Additional information: Quantity limitations 	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· ADR/ADN · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 50 ml
 Transport category Tunnel restriction code 	2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2
	(Contd. on page

EU-EN



Printing date 20.05.2023

Version number 15 (replaces version 14)

Revision: 06.05.2023

Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

(Contd. of page 8)

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":

UN 1133 ADHESIVES SOLUTION, 3, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H400 Very toxic to aquatic life.

(Contd. on page 10)



Printing date 20.05.2023

Version number 15 (replaces version 14)

Revision: 06.05.2023

(Contd. of page 9)

Trade name: UHU PLUS MULTIFEST YE SY 50ML*6 DE

H410 Very toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) I	No 1272/2008
Flammable liquids	Bridging principles
Skin sensitisation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
Department issuing SDS: UHU QESH Contact: UHU QESH Date of previous version: 12.02.2022 Version number of previous version: 14 Abbreviations and acronyms: ADR: Accord relatif au transport international des marchan the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Lat EINECS: European Inventory of Existing Commercial Chem ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American EC50: Lethal concentration, 50 percent D50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) · Aquatic Acute 1: Hazardous to the aquatic environment - ac Aquatic Chronic 1: Hazardous to the aquatic environment - 1 * Data compared to the previous version alte	- Category 3 sute aquatic hazard – Category 1 long-term aquatic hazard – Category 1