

Page 1/10

### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 20

Revision: 26.06.2019

#### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

- · Trade name: UHU extra Alleskleber flex & clean
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0 email: sds@uhu.boltongroup.com

• Further information obtainable from: UHU QESH • 1.4 Emergency telephone number: Tel.: + 49 (0) 30/19240 (Notruf)

Tel.: + 49 (0) 72 23/28 40

England and Wales (NHS Direct) 111 Schottland (NHS 24) 111

#### **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements
 Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



· Signal word Danger

Fax: 0049-(0)7223-284-245



Page 2/10

#### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 20

Revision: 26.06.2019

#### Trade name: UHU extra Alleskleber flex & clean

methyl acetate	
· Hazard statements	
H225 Highly flammable liquid and vapour.	
H336 May cause drowsiness or dizziness.	
· Precautionary statements	
P101 If medical advice is needed, have product container or label at hand.	
P102 Keep out of reach of children.	
P210 Keep away from open flames No smoking.	
P261 Avoid breathing vapours.	
P501 Dispose of contents/container in accordance with national regulations.	
2.3 Other hazards	
Results of PBT and vPvB assessment	
· <b>PBT:</b> Not applicable.	
· vPvB: Not applicable.	
· · · · · · · · · · · · · · · · · · ·	

#### · 3.2 Mixtures

#### Description:

Mixture of substances listed below with nonhazardous additions.

Adhesive

# Dangerous components: methyl acetate CAS: 79-20-9 methyl acetate EINECS: 201-185-2 Image: Flam: Liq. 2, H225; Image: Flam: Liq. 2, H319; STOT Reg.nr.: 01-2119459211-47-XXXX SE 3, H336

CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43 ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319

Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

#### · 4.1 Description of first aid measures

- · General information: No special measures required.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)

25-50%

25-50%

EU-EN



Page 3/10

#### Safety data sheet

#### according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 20

Revision: 26.06.2019

#### Trade name: UHU extra Alleskleber flex & clean

(Contd. of page 2) • **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

#### **SECTION 5: Firefighting measures**

5.1 Extinguishing media

· Suitable extinguishing agents:

- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Send for recovery or disposal in suitable receptacles. Ensure adequate ventilation. Pick up mechanically.
- Pick up mechanically.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

#### · 7.1 Precautions for safe handling

- Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- **Information about fire and explosion protection:** Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep container tightly sealed.

(Contd. on page 4)

EU-EN



Page 4/10

#### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 20

Revision: 26.06.2019

(Contd. of page 3)

#### Trade name: UHU extra Alleskleber flex & clean

Store in cool, dry conditions in well sealed receptacles.

• Storage class: 3

• 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

• Additional information about design of technical facilities: No further data; see item 7.

AGW (Germany) Long-term value: 620 mg/m³, 200 ppm 2(I);DFG, AGS, Y			
64-17-5 e	thanol		
AGW (Ge		ong-term value: 380 mg/m³, 2 II);DFG, Y	00 ppm
DNELs			
79-20-9 m	nethyl ace	tate	
Oral	Consume	er DNEL, longterm oral	44 mg/kg bw/day (.)
Dermal	Consume	er DNEL, longterm dermal	44 mg/kg bw/day (.)
Inhalative	Consume	er DNEL, longterm inhalation	131 mg/m³ (.)
64-17-5 e	thanol		1
Oral	Consume	er DNEL, longterm oral	87 mg/kg bw/day (.)
Dermal	Consume	er DNEL, longterm dermal	206 mg/kg bw/day (.)
Inhalative	e Consumer DNEL, acute inhalation		950 mg/m³ (.)
	Consumer DNEL, longterm inhalation		114 mg/m³ (.)
PNECs	·		L
79-20-9 m	nethyl ace	tate	
PNEC Fre	esh water	0.12 mg/l (.)	
PNEC Ma	rine water	0.012 mg/l (.)	
64-17-5 e	thanol	I	
PNEC Fre	esh water	0.96 mg/l (.)	
PNEC Marine water		0.79 mg/l (.)	
	al informa	tion: The lists valid during the	e making were used as basis.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

(Contd. on page 5)

EU-EN



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019


Version number 20

Revision: 26.06.2019

Page 5/10

EU-EN

#### Trade name: UHU extra Alleskleber flex & clean



9.1 Information on basic physica General Information	al and chemical properties	
Appearance:		
Form:	Structurally viscous	
Colour:	Colourless	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling	range: 57 °C	
Flash point:	-10 °C	
Flammability (solid, gas):	Not applicable.	



Page 6/10

### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 20

Revision: 26.06.2019

#### Trade name: UHU extra Alleskleber flex & clean

	(Contd. of page 5)
· Ignition temperature:	425 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits: Lower:	3.1 Vol %
Upper:	16 Vol %
· Vapour pressure at 20 °C:	220 hPa
<ul> <li>Density at 20 °C:</li> <li>Relative density</li> <li>Vapour density</li> <li>Evaporation rate</li> </ul>	0.95 g/cm <sup>3</sup> Not determined. Not determined. Not determined.
<ul> <li>Solubility in / Miscibility with water:</li> </ul>	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
<ul> <li>Viscosity:</li> <li>Dynamic at 20 °C:</li> <li>Kinematic:</li> </ul>	90000 mPas Not determined.
<ul> <li>Solvent content:</li> <li>Organic solvents:</li> <li>Water:</li> <li>VOC (EC)</li> </ul>	68.8 % 0.4 % 68.85 %
Solids content: • 9.2 Other information	30.8 % All relevant physical data were determined for the mixture. All non determined data are not measurably or not relevant for the characterization of the mixture.

#### **SECTION 10: Stability and reactivity**

• **10.1 Reactivity** No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 7) EU-EN



Page 7/10

#### Safety data sheet

#### according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 20

Revision: 26.06.2019

#### Trade name: UHU extra Alleskleber flex & clean

(Contd. of page 6) • **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

#### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

#### 79-20-9 methyl acetate

LD50 3705 mg/kg (rabbit)

#### 64-17-5 ethanol

Oral

Oral LD50 7060 mg/kg (rat)

Inhalative LC50/4 h 20000 mg/l (rat)

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- $\cdot$  Carcinogenicity Based on available data, the classification criteria are not met.
- $\cdot$  Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow product to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

(Contd. on page 8)

EU-EN



Page 8/10

#### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 20

Revision: 26.06.2019

#### Trade name: UHU extra Alleskleber flex & clean

(Contd. of page 7)

#### **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

#### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

#### · European waste catalogue

08 04 09\* waste adhesives and sealants containing organic solvents or other hazardous substances

#### · Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1133
14.2 UN proper shipping name ADR IMDG, IATA	1133 ADHESIVES 1133 KLEBSTOFFE, Sondervorschrift 640H ADHESIVES
14.3 Transport hazard class(es)	ADILOIVES
ADR, IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	Νο
• 14.6 Special precautions for user • Danger code (Kemler): • EMS Number: • Stowage Category	Warning: Flammable liquids. - F-E,S-D A
14.7 Transport in bulk according to Anr of Marpol and the IBC Code	nex II Not applicable.

EU-EN



Page 9/10

#### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 20

Revision: 26.06.2019

#### Trade name: UHU extra Alleskleber flex & clean

· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
Transport category	3
Tunnel restriction code	E
·IMDG	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
UN "Model Regulation":	UN 1133 ADHESIVES, 3, III

#### **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- · Department issuing SDS: UHU QESH
- · Contact: Dr. C. Hanf
- Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 10)



Page 10/10

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019

Version number 20

Revision: 26.06.2019

#### Trade name: UHU extra Alleskleber flex & clean

	(Contd. of page 9)
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
VOC: Volatile Organic Compounds (USA, EU)	
DNEL: Derived No-Effect Level (REACH)	
PNEC: Predicted No-Effect Concentration (REACH)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 2: Flammable liquids – Category 2	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
* Data compared to the previous version altered.	
	EU-EN-