

Printing date 12.10.2018

Version number 17

Revision: 18.04.2018

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

. 1.1 Product identifier


. Trade name: GRIFFON DEVMOR AER 300ML*12 L1

- . **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- . Application of the substance / the mixture Metal-working product

. 1.3 Details of the supplier of the safety data sheet

Manufacturer(1)/Supplier(2): 1 Bison International Dr.A.F.Philipsstraat 9 NL-4462 EW Goes PO Box 160 NL-4460 AD Goes tel. +31 88 3235700 fax. +31 88 3235800 e mail: sds@boltonadhesives.com

. Further information obtainable from: Bison QESH . 1.4 Emergency telephone number: +31 88 3235700





Printing date 12.10.2018

Version number 17

Revision: 18.04.2018

Trade name: GRIFFON DEVMOR AER 300ML*12 L1

(Contd. of page 1) propan-2-ol . Hazard statements H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation. H319 H336 May cause drowsiness or dizziness. . Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing spray. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with national regulations. . 2.3 Other hazards . Results of PBT and vPvB assessment . PBT: Not applicable. . vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

. 3.2 Mixtures

. Description: Metal working product

butane ♦ Flam. Gas 1, H220; ♦ Acute Tox. 3, H331; Press. Gas C, H280	25-50%
acetone	10-25%
propan-2-ol Flam. Liq. 2, H225;	10-25%
propane Flam. Gas 1, H220; Press. Gas C, H280	10-25%
isobutane � Flam. Gas 1, H220; Press. Gas C, H280	2.5-10%
	 Flam. Gas 1, H220; Acute Tox. 3, H331; Press. Gas C, H280 acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336 propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336 propane Flam. Gas 1, H220; Press. Gas C, H280 isobutane

SECTION 4: First aid measures

. 4.1 Description of first aid measures

- . General information: No special measures required.
- . After inhalation: Supply fresh air; consult doctor in case of complaints.
- . After skin contact: Generally the product does not irritate the skin.

(Contd. on page 3)

www.griffon.eu



Printing date 12.10.2018

Version number 17

Revision: 18.04.2018

Trade name: GRIFFON DEVMOR AER 300ML*12 L1

. After eye contact:

(Contd. of page 2)

- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. **After swallowing:** Do not induce vomiting; call for medical help immediately.
- . 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

. 5.1 Extinguishing media

- . Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- . 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- . 5.3 Advice for firefighters
- . Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- . **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- . 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- . 6.3 Methods and material for containment and cleaning up:
- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.

. 6.4 Reference to other sections

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

. 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

. Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

. 7.2 Conditions for safe storage, including any incompatibilities

- . Storage:
- Requirements to be met by storerooms and receptacles:
 Observe official regulations on storing packagings with pressurised containers.
 Information about storage in one common storage facility: Not required.
- . Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 4)



Printing date 12.10.2018

Version number 17

Revision: 18.04.2018

(Contd. of page 3)

Trade name: GRIFFON DEVMOR AER 300ML*12 L1

. 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

. Additional information about design of technical facilities: No further data; see item 7.

. 8.1 Control parameters

. Ingredients with limit values that require monitoring at the workplace:				
106-97-8 butane				
WEL (Great Britain)	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)			
67-64-1 acetone				
WEL (Great Britain)	Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm			
IOELV (European Union)	Long-term value: 1210 mg/m³, 500 ppm			
67-63-0 propan-2-ol				
WEL (Great Britain)	Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm			

. Additional information: The lists valid during the making were used as basis.

. 8.2 Exposure controls

- . Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

. Respiratory protection: Not required.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Recommended thickness of the material: > 0,12 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Nitrile rubber, NBR

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

(Contd. on page 5)

³⁻EN -



Printing date 12.10.2018

Version number 17

Revision: 18.04.2018

(Contd. of page 4)

Trade name: GRIFFON DEVMOR AER 300ML*12 L1

. Eye protection:

Tightly sealed goggles

9.1 Information on basic physical and chemical properties General Information		
Appearance: Form: Colour: Odour: Odour threshold:	Aerosol According to product specification Characteristic Not determined.	
pH-value:	Not determined.	
Change in condition Melting point/freezing point: Undetermined. Initial boiling point and boiling range: -44 °C		
Flash point:	-97 °C	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	365 °C	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Not determined.	
Explosion limits: Lower: Upper:	1.5 Vol % 13 Vol %	
Vapour pressure at 20 °C:	8,300 hPa	
Density at 20 °C: Relative density Vapour density Evaporation rate	0.8109 g/cm ³ Not determined. Not determined. Not applicable.	
Solubility in / Miscibility with water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity: Dynamic: Kinematic: Organis solvents:	Not determined. Not determined. 90.3 %	

GB-EN



Printing date 12.10.2018

Version number 17

Revision: 18.04.2018

(Contd. of page 5)

Trade name: GRIFFON DEVMOR AER 300ML*12 L1

. 9.2 Other information

All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

SECTION 10: Stability and reactivity

. 10.1 Reactivity No further relevant information available.

. 10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

. 10.3 Possibility of hazardous reactions No dangerous reactions known.

. 10.4 Conditions to avoid No further relevant information available.

. 10.5 Incompatible materials: No further relevant information available.

. **10.6 Hazardous decomposition products:** Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

. 11.1 Information on toxicological effects

. Acute toxicity Based on available data, the classification criteria are not met.

. LD/LC50 values relevant for classification:

106-97-8 butane

Inhalative LC50/4 h 658 mg/l (rat)

67-64-1 acetone

Oral LD50 5,800 mg/kg (rat)

Dermal LD50 20,000 mg/kg (rbt)

67-63-0 propan-2-ol

Oral	LD50	4,570 mg/kg (rat)
		13,400 mg/kg (rab)
Inhalative	LC50/4 h	30 mg/l (rat)

Primary irritant effect:

. Skin corrosion/irritation Based on available data, the classification criteria are not met.

. Serious eye damage/irritation

Causes serious eye irritation.

. Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

. CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

. Germ cell mutagenicity Based on available data, the classification criteria are not met.

. Carcinogenicity Based on available data, the classification criteria are not met.

. Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

. STOT-repeated exposure Based on available data, the classification criteria are not met.

. Aspiration hazard Based on available data, the classification criteria are not met.

GB-EN (Contd. on page 7)



Printing date 12.10.2018

Version number 17

Revision: 18.04.2018

Trade name: GRIFFON DEVMOR AER 300ML*12 L1

(Contd. of page 6)

SECTION 12: Ecological information

. 12.1 Toxicity

- . Aquatic toxicity: No further relevant information available.
- . 12.2 Persistence and degradability No further relevant information available.
- . 12.3 Bioaccumulative potential No further relevant information available.
- . **12.4 Mobility in soil** No further relevant information available.
- Additional ecological information:
- . General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- . 12.5 Results of PBT and vPvB assessment
- . **PBT:** Not applicable.
- . vPvB: Not applicable.
- . 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

. 13.1 Waste treatment methods

. Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

. Uncleaned packaging:

. Recommendation:

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN-Number		
ADR/ADN, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR/ADN	1950 AEROSOLS	
IMDG	AEROSOLS	
ΙΑΤΑ	AEROSOLS, flammable	
14.3 Transport hazard class(es)		
ADR/ADN		
Class	2 5F Gases.	



Printing date 12.10.2018

Version number 17

Revision: 18.04.2018

Trade name: GRIFFON DEVMOR AER 300ML*12 L1

	(Contd. of page
. Label	2.1
. IMDG, IATA	
. Class . Label	2.1 2.1
. 14.4 Packing group . ADR/ADN, IMDG, IATA	Void
. 14.5 Environmental hazards: . Marine pollutant:	No
. 14.6 Special precautions for user	Warning: Gases.
. Danger code (Kemler): . EMS Number:	
. Stowage Code	F-D,S-U SW1 Protected from sources of heat.
. otowage oode	SW22 For AEROSOLS with a maximum capacit of 1 litre: Category A. For AEROSOLS with capacity above 1 litre: Category B. For WAST AEROSOLS: Category C, Clear of living quarters.
. Segregation Code	SG69 For AEROSOLS with a maximum capacit of 1 litre: Segregation as for class 9. Sto "separated from" class 1 except for division 1.4 For AEROSOLS with a capacity above 1 litre Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation a for the appropriate subdivision of class 2.
. 14.7 Transport in bulk according to Anne of Marpol and the IBC Code	ex II Not applicable.
Transport/Additional information:	
. ADR/ADN	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
Transport octors.	Not permitted as Excepted Quantity
. Transport category . Tunnel restriction code	2 D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
Demonster	Not permitted as Excepted Quantity
. Remarks:	Under certain conditions substances in Class (flammable liquids) can be classified i packinggroup III.
	See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2



Printing date 12.10.2018

Version number 17

Revision: 18.04.2018

(Contd. of page 8)

Trade name: GRIFFON DEVMOR AER 300ML*12 L1

. UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- . 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- . Directive 2012/18/EU
- . Named dangerous substances ANNEX I None of the ingredients is listed.
- . Seveso category P3a FLAMMABLE AEROSOLS
- . Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

. Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H336 May cause drowsiness or dizziness.

. Department issuing SDS: Bison QESH

Contact: Reach coördinator

. Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases - Category 1 Aerosol 1: Aerosols - Category 1 Press. Gas C: Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Acute Tox. 3: Acute toxicity - Category 3 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 . * Data compared to the previous version altered.

GB-EN -