

UHU® SUPER GLUE PIPETTE

SMART PIPETTE CONTAINER FOR PRECISE DOT-BY-DOT GLUEING



PRODUCT DESCRIPTION

Ultra-fast and extremely strong liquid super glue in a solid, safe-standing container with Direct-Stop-Technology and a thin dosing nozzle. Ensures controlled, non-drip glueing with utmost precision. Dishwasher proof and water resistant.

FIELD OF APPLICATION

Ideal for small-area bonds. Glues almost all solid and flexible materials such as many plastics (such as rigid PVC, ABS, PS, Plexiglas®, polycarbonate (Makrolon®), and phenolic resins (Bakelite®)), leather, porcelain, ceramics, metal, wood, cork, felt, cloth (check suitability first), and rubber. Only partly suitable for glass (over a certain period of time the bond becomes brittle, causing it to weaken). Not suitable for PE, PP, silicone resins and rubbers, PTFE, styrofoam, fabrics and leather clothing.

PROPERTIES

- Ultra fast and extremely strong super glue
- With Direct-Stop-Technology and thin nozzle for precise dosing
- Flows into smallest corners and joints
- Dishwasher proof and water resistant
- Safe-standing container

PREPARATION

Working conditions: Do not use at temperatures below +10°C. The glue responds best to an air humidity level of 50-70%.

Surface requirements: Surfaces to be glued must be clean, dry, and free of dust and grease, and must fit exactly.

APPLICATION

Directions for use:

1. To pierce the membrane, turn the whole cap clockwise firmly onto the container. 2. Unscrew the top cap to reveal applicator. Apply a thin layer of adhesive to one side. Press parts together immediately. After use: Clean nozzle with a dry tissue and replace cap. Store in a cool, dry place.

Stains/residue: Wipe off excess glue immediately with a dry cloth. After curing, glue residue is very difficult to remove. Acetone will dissolve glue but very slowly (check suitability first).

Advice: When glueing at low humidity, curing time can be shortened by briefly breathing onto one of the parts to be assembled. The best glueing results are reached at room temperature.

Points of attention: Contains cyanoacrylate. Bonds skin and eyelids together in seconds. If product comes into contact with the eyes, rinse immediately with plenty of water and seek medical advice. In case of contact with skin, glue can be dissolved by soaking in warm soapy water. Then apply a skin cream. May cause respiratory irritation. Avoid breathing vapours. Keep out of the reach of children.

CURE TIMES*

Final bonding strength after: approx. 12 hours

* Curing time may vary depending on a.o. surface, product quantity used, humidity level and ambient temperature.

TECHNICAL SPECIFICATIONS

Appearance: colourless, clear

Chemical base: cyanoacrylic-acid-ethylester

Consistency: Liquid

Viscosity: approx. 0.50 mPa.s.

Density: approx. 1,07 g/cm³

STORAGE CONDITIONS

Store in a dry, cool, frost-free place. Storage below +5°C (in refrigerator) ensures maximum shelf life.

PHYSIOLOGICAL PROPERTIES

Cyanoacrylate adhesives are to a great extent considered to be physiologically safe.

PACK SIZES

Pipette 3g, 10g