

# UHU POR

## QUICK-SETTING SPECIAL ADHESIVE

# UHU



### TECHNISCHE SPECIFICATIES

**Viscositeit:** ca. 120-150 mPa.s.

**Bijzondere specificaties:**

Appearance: slightly yellowish, clear

Consistency: Medium viscosity

Solvent: Aliphatic solvent mixture

Solid content [%]: approx. 32

Flashpoint [°C]: approx. -5

Danger class (VbF): A I

### VERPAKKINGSGROOTTES

tube 40g

### PRODUCTOMSCHRIJVING

UHU por is a quick-drying contact adhesive, which was specially developed for the bonding of polystyrene foam (e.g. Styropor®).

UHU por provides a fast-setting, rubbery adhesive film with a long period of adhesion and a rapid setting capacity. The composition of its solvents is such that the structure of the polystyrene foam is not attacked.

### TOEPASSINGSGBIED

the bonding of hard foam materials to each other, and also to wood, wood materials, paper, cardboard, textiles, metals and numerous plastics, gluing photos also special papers coated with PE, PP, e.g. photographic paper.

### EIGENSCHAPPEN

The adhesive film is neutral (acid- and alkali-free), almost colourless and water-resistant.

Approximately 150-250 g/m<sup>2</sup> UHU por are required for surface bonds, depending on the quality of the surfaces.

### VOORBEREIDING

**Persoonlijke bescherming:** UHU por contains volatile, easily inflammable solvents, appropriate precautions should therefore be taken during working and storage.

**Eisen oppervlakken:** The surfaces for bonding must be clean, dry and free of oil and grease.