

UHU® PORCELAIN SPECIAL ADHESIVE

WHITE LIQUID PORCELAIN REPAIR ADHESIVE



PRODUCT DESCRIPTION

White liquid porcelain repair, the outstanding adhesive for bonding, sealing and mending porcelain, marble, stoneware, and ceramics.
Resistant to hot water, usual household cleaners and diluted bases.

FIELD OF APPLICATION

gluing, sealing and repairing porcelain, marble, stoneware and ceramics. Not suitable for PE, PP, silicone resins and rubbers, PTFE, styrofoam, fabrics and leather clothing.

PROPERTIES

- resistant to hot water
- temperature resistant

PREPARATION

Personal safety: UHU Porcelain contains volatile, highly flammable solvents; precautions are therefore necessary during use and storage. Ensure proper ventilation when using over large areas.

Surface requirements: Surfaces that are to be repaired must be clean, dry and free of oil, grease and dust.

APPLICATION

Dilute: Light petrol

Directions for use:

Apply the glue to both sides of fracture and leave to dry. Then apply another coat of adhesive to one side and press parts together immediately. Leave to dry for 24 hours. Items such as crockery should be rinsed in hot water before use.

Stains/residue: Specks can be removed with acetone.

Advice: If necessary the adhesive may be diluted with acetone.

Points of attention: The product contains volatile, highly flammable solvents; precautions are therefore necessary during use and storage. Ensure proper ventilation when using over large areas.

CURE TIMES*

Final bonding strength after: approx. 24 hours

* Curing time may vary depending on a.o. surface, product quantity used, humidity level and ambient temperature.

TECHNICAL PROPERTIES

Water resistance: Good

Temperature resistance: +80°

Chemicals resistance: Good

Paintability: Good

TECHNICAL SPECIFICATIONS

Appearance: White liquid

Chemical base: Synthetic Nitro Resins

Bonding technique: 2-sided application

Colour: White

Consistency: Medium viscosity

Viscosity: approx. Liquid

Solid matter: approx. 52 %

Density: approx. 0.95 g/cm³

Specifications: Flame point [°C]: +21

Danger class (VbF): A 1

STORAGE CONDITIONS

Store the product in a cool but frost-free place.

PHYSIOLOGICAL PROPERTIES

The dried adhesive is inert, completely neutral and physiologically indifferent.

PACK SIZES

tube 30g