

LUFTENTFEUCHTER ORIGINAL

FIGHTS MOISTURE IN SPACES WITH LITTLE OR NO VENTILATION.

UHU



PRODUCT DESCRIPTION

Fights condensation, moisture and stale smells in spaces with little or no ventilation.

FIELD OF APPLICATION

Lowers high levels of relative humidity in closed spaces with little or no ventilation. Suitable for caravan, boat, barn, meter cupboard, attic, pantry, basement, crawl space, guest room, wardrobe, gazebo, kitchen, safe and laundry room.

PROPERTIES

- Suitable for all UHU® refills: UHU® Refill bag and UHU® Tab
- Protects your valuables against moisture
- Uses no energy
- Refreshes the air
- Works clean

APPLICATION

Coverage: 1 kg works for approximately 3 months in a room up to approximately 100 m³ and absorbs with a filling of 1 kg approximately 1 Litre of water, depending on the temperature, humidity and size of the room.

Directions for use:

User instructions for refilling with UHU® Refill.

Remove the white cap from the device and place the refill bag in the container. Place the white cap back and UHU® Moisture Absorber is ready for use. When the refill has dissolved completely, the device can easily be emptied in the toilet or sink. The empty refill bag can be thrown into the waste container.

Always place the UHU® device on a flat stable surface, preferably in a washtub.

Stains/residue: Spilt fluid can cause surface marks. These spots continue to

attract moisture. Remove stains with an abundance of water. Remove stains in textiles (floor coverings, lining) can be removed with sodium sulphate (available on request at Bison International). Make a 5% solution with water (50 g/l) and spread it over the stain. Approx. for approx. 30 minutes. Then dry it off using a hairdryer or electric heater. Remove the remaining powder with a vacuum cleaner. Repeat the process if necessary. Rinse wash basin or sink well with water.

Advice: Always place the UHU® Moisture Absorber Original on a flat and stable surface.

Points of attention: At lower temperatures the Moisture Absorber works more slowly and clumping can occur. Increasing the temperature will speed up the working again. Avoid contact with leather, wood, stone and metal, as these materials can be affected negatively.

TECHNICAL SPECIFICATIONS

Chemical base: Calcium chloride

Colour: White

pH-value: approx. 10

Specifications:

Water absorption: about 1 gram of water per gram of salt.

STORAGE CONDITIONS

At least 24 months after date of manufacture.