

# LUFTENTFEUCHTER ORIGINAL

## FIGHTS MOISTURE IN SPACES WITH LITTLE OR NO VENTILATION.

# UHU



### PRODUCT DESCRIPTION

Fights condensation, moisture and stale smells in spaces with little or no ventilation.

### FIELD OF APPLICATION

Lowers high levels of relative humidity in closed spaces with little or no ventilation. Suitable for caravan, boat, barn, meter cupboard, attic, pantry, basement, crawl space, guest room, wardrobe, gazebo, kitchen, safe and laundry room.

### PROPERTIES

- Suitable for all UHU® refills: UHU® Refill bag and UHU® Tab
- Protects your valuables against moisture
- Uses no energy
- Refreshes the air
- Works clean

### APPLICATION

**Coverage:** 450 g works for approximately 3 months in a room up to approximately 30 m<sup>3</sup> and absorbs with a filling of 450 g approximately 0.5 litres of water, depending on the temperature, humidity and size of the room.

#### Directions for use:

User instructions for refilling with UHU® Refill.

Remove the white cap of the UHU® device and place the refill bag in the receptacle. Place the white cap back and UHU® is ready for use. When the refill has dissolved completely, the UHU® device can easily be emptied in the toilet or sink. The empty refill bag can be thrown into the waste container.

User instructions for refilling with UHU® Tab 500 g.

Cut the plastic bag open carefully. Remove the cap of the device and place the

Tab in the device. Use one Tab for the device 450 g (suitable for spaces up to 30 m<sup>3</sup>). Put the cap back and the moisture absorber is ready for use.

When the Tab has dissolved completely, the UHU® device can easily be emptied in the toilet or sink.

Always place the UHU® device on a flat stable surface, preferably in a washtub.

**Stains/residue:** Spilt fluid can cause surface marks. These spots continue to attract moisture. Remove stains with an abundance of water. Remove stains in textiles (floor coverings, lining) can be removed with sodium sulphate (available on request at Bison International). Make a 5% solution with water (50 g/l) and spread it over the stain. Approx. for approx. 30 minutes. Then dry it off using a hairdryer or electric heater. Remove the remaining powder with a vacuum cleaner. Repeat the process if necessary. Rinse wash basin or sink well with water.

**Advice:** Always place the UHU® Moisture Absorber Original on a flat and stable surface.

**Points of attention:** At lower temperatures the Moisture Absorber works more slowly and clumping can occur. Increasing the temperature will speed up the working again. Avoid contact with leather, wood, stone and metal, as these materials can be affected negatively.

### TECHNICAL SPECIFICATIONS

**Chemical base:** Calcium chloride

**Colour:** White

**pH-value:** approx. 10

**Specifications:**

Water absorption: about 1 gram of water per gram of salt.

### STORAGE CONDITIONS

At least 24 months after date of manufacture.