

UHU® REPAIR ALL KRAFTBAND

SUPER-STRONG FABRIC REPAIR TAPE



TECHNICAL SPECIFICATIONS

Appearance: grey/ silver

Specifications: Backing: PE film with fabric

Adhesive: rubber

Total thickness: 170 µm

Adhesion to steel: 9 N/ 25 mm

Tensile strength: 95 N/ 25 mm

STORAGE CONDITIONS

Store in a cool, dry place out of direct sunlight.

PRODUCT DESCRIPTION

Super-strong textile tape with polyester coating for waterproof repairing, packing, sealing, connecting and strengthening. Adheres to almost all surfaces, like e.g. stone, concrete, wood and many plastics. Suitable for indoor and outdoor use thanks to its UV-stability and resistance to temperatures of between -15°C and +70°C. Can be torn off manually and written on.

FIELD OF APPLICATION

For waterproof repairing, strengthening, sealing, connecting and protecting, indoors and outdoors. Adheres to metal, stone, concrete, wood and plastics. Super-strong duct tape for a universal use.

PROPERTIES

- Super strong
- Extra initial high tack
- Universal
- Indoor and Outdoor
- Temperature resistant
- Waterproof
- UV resistant
- Can be torn off manually

PREPARATION

Surface requirements: The surface must be clean, dry and free of dust and grease.

APPLICATION

Directions for use:

Stick the tape onto the object without touching the adhesive.

Note: This information is the result of carefully executed tests. This Technical Data Sheet has been prepared to the best of our knowledge to provide you with advice when gluing. We cannot be held responsible for the results or any damage suffered, as the variety of factors involved (type and combination of materials and working method) are beyond our control. Users have to carry out their own checks and trials. Liability can only be accepted for the consistently high quality of our product.