

**Stains/residue:** Remove any remaining adhesive mechanically and, if necessary, clean the surfaces with acetone. The pad can only be removed completely from smooth, solid, insensitive substrates.

**Points of attention:** Do not touch the adhesive as this reduces the tape's adhesive strength.

# TECHNICAL PROPERTIES Water resistance: Very good

## **TECHNICAL SPECIFICATIONS**

**Appearance:** white adhesive pads **Specifications:** Liner: white silicone paper

Adhesive: synthetic rubber

Carrier: PE foam

Thickness without liner [µm]: 1.600 90° peel strength on steel (N/25 mm): 20

### STORAGE CONDITIONS

Store in a dry, cool and frost-free place.

#### **PACK SIZES**

Blister: 56 adhesive pads Box: 50 adhesive pads

# **PRODUCT DESCRIPTION**

Strong, double-sided adhesive pads for a fast, clean and permanent fixation of many small things without nails, screws or pins. For household use, hobby and office.

#### **FIELD OF APPLICATION**

Affixes small objects on metal, glass, plastic materials, fabric, paper, cardboard, etc.

#### **PROPERTIES**

- · double-sided adhesive pads
- · strong: up to 300g/pad
- · immediate and permanent
- · temperature resistant

# **PREPARATION**

**Working conditions:** The minimum working temperature is 10°C.

Surface requirements: The surface must be clean, dry and free of dust and

grease.

**Preliminary surface treatment:** For best results, first cleanse the surfaces to be glued (e.g. with alcohol or white spirit).

#### **APPLICATION**

## **Directions for use:**

Stick the adhesive pad onto the object to be fixed. Remove the protective film without touching the adhesive. Affix the object to the desired spot and press hard.

Note: This information is the result of carefully executed tests. This Technical Data Sheet has been prepared to the best of our knowledge to provide you with advice when gluing. We cannot be held responsible for the results or any damage suffered, as the variety of factors involved (type and combination of materials and working method) are beyond our control. Users have to carry out their own checks and trials. Liability can only be accepted for the consistently high quality of our product.