

FIX

STRONG, DOUBLE-SIDED ADHESIVE PADS

UHU



Points of attention: Do not touch the adhesive as this reduces the tape's adhesive strength.

TECHNICAL PROPERTIES

Water resistance: Very good

TECHNICAL SPECIFICATIONS

Appearance: white adhesive pads

Specifications:

Liner: white silicone paper

Adhesive: synthetic rubber

Carrier: PE foam

Thickness without liner [µm]: 1.600

90° peel strength on steel (N/25 mm): 20

STORAGE CONDITIONS

Store in a dry, cool and frost-free place.

PACK SIZES

Blister: 56 adhesive pads

Box: 50 adhesive pads

PRODUCT DESCRIPTION

Strong, double-sided adhesive pads for a fast, clean and permanent fixation of many small things without nails, screws or pins. For household use, hobby and office.

FIELD OF APPLICATION

Affixes small objects on metal, glass, plastic materials, fabric, paper, cardboard, etc.

PROPERTIES

- double-sided adhesive pads
- strong: up to 300g/pad
- immediate and permanent
- temperature resistant

PREPARATION

Working conditions: The minimum working temperature is 10°C.

Surface requirements: The surface must be clean, dry and free of dust and grease.

Preliminary surface treatment: For best results, first cleanse the surfaces to be glued (e.g. with alcohol or white spirit).

APPLICATION

Directions for use:

Stick the adhesive pad onto the object to be fixed. Remove the protective film without touching the adhesive. Affix the object to the desired spot and press hard.

Stains/residue: Remove any remaining adhesive mechanically and, if necessary, clean the surfaces with acetone. The pad can only be removed completely from smooth, solid, insensitive substrates.

Note: This information is the result of carefully executed tests. This Technical Data Sheet has been prepared to the best of our knowledge to provide you with advice when gluing. We cannot be held responsible for the results or any damage suffered, as the variety of factors involved (type and combination of materials and working method) are beyond our control. Users have to carry out their own checks and trials. Liability can only be accepted for the consistently high quality of our product.