



SPRAY ADHESIVE 3IN1

PERMANENT – CORRECTABLE – REMOVABLE



PRODUCT DESCRIPTION

UHU Spray Adhesive 3in1 is a universal adhesive for large surface bonding. Bonds alternatively permanent, corrigible or removable. Suitable for bonding various materials, also suitable for Styrofoam®. Even spray pattern – powerful glue application. Non-clog spray valve.

FIELD OF APPLICATION

For bonding paper, cardboard, collages, metal foils, leather, felt, many plastics, textiles, Styrofoam® etc. with themselves and many other materials such as wood, ceramics, glass etc. Not suitable for PE, PP.

PROPERTIES

- Universal
- Strong
- Fast
- Bonds alternatively:
 1. permanent
 2. correctable
 3. removable

PREPARATION

Working conditions: Do not use at temperatures below +10 °C.

Personal safety: UHU SPRAY ADHESIVE 3 in 1 contains volatil, highly inflammable solvents. Therefore there must be taken adequate precautions when handling and storing. When bonding larger surfaces make sure that the workplace is well ventilated.

Surface requirements: The areas to be glued must be dry and free of any dust or grease.

APPLICATION

Directions for use:

Shake can before use. Make sure the distance between the spray nozzle and the material to be coated is 20-25 cm. Spray on the adhesive fine and constantly.

Glues:

1. permanent: Apply a thin, even coat to both surfaces. Wait for at least 10 min., then press the parts together firmly. Bonds immediately – correcting is no longer possible! The greater the pressure, the better the bonding result. The duration of the pressure is not essential for the strength of the bonding.

2. corrigible: Apply a thin, even coat to one part only and join the two parts immediately. Afterwards the position of the parts can be adjusted up to 5 min. Then the bond is permanent.

Drying time – depending on temperature and material – up to 24 h.
One of both surfaces must be absorbent or porous!

3. removable: Apply a thin, even coat to the part that is desired to remain removable and wait for at least 20 min. Afterwards the part is self-adhesive and can be fixed and removed several times.

Stains/residue: For cleaning smudgy parts and equipment as well as for removing stains use cleaning spirit. Cured adhesive stains are hard to remove.

Points of attention: Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Throw away only when completely empty. Do not breathe vapour. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition – Do not smoke. Without adequate ventilation accumulation of potentially explosive alloys possible. Keep out of reach of children.

TECHNICAL PROPERTIES

Temperature resistance: -40°C to +50°C

TECHNICAL SPECIFICATIONS

Appearance: light yellow

Chemical base: styrene butadiene rubber (SBR)

Density: approx. 0,75 without fuel gas g/cm³

STORAGE CONDITIONS

Product should be stored in a dry, cool and frost free place.

PACK SIZES

UHU SPRAY ADHESIVE 3 in 1 is available in can of 200ml or 500ml.