

# UHU<sup>®</sup> SPRAY ADHESIVE 3 IN 1

## PERMANENT – CORRECTABLE – REMOVABLE



### PRODUCT DESCRIPTION

UHU Spray Adhesive 3in1 is a universal adhesive for large surface bonding. Bonds alternatively permanent, corrigible or removable. Suitable for bonding various materials, also suitable for Styrofoam<sup>®</sup>. Even spray pattern – powerful glue application. Non-clog spray valve.

### FIELD OF APPLICATION

For bonding paper, cardboard, collages, metal foils, leather, felt, many plastics, textiles, Styrofoam<sup>®</sup> etc. with themselves and many other materials such as wood, ceramics, glass etc. Not suitable for PE, PP.

### PROPERTIES

- Universal
- Strong
- Fast
- Bonds alternatively:
  1. permanent
  2. correctable
  3. removable

### PREPARATION

**Working conditions:** Do not use at temperatures below +10 °C.

**Personal safety:** UHU SPRAY ADHESIVE 3 in 1 contains volatil, highly inflammable solvents. Therefore there must be taken adequate precautions when handling and storing. When bonding larger surfaces make sure that the workplace is well ventilated.

**Surface requirements:** The areas to be glued must be dry and free of any dust or grease.

### APPLICATION

#### Directions for use:

Shake can before use. Make sure the distance between the spray nozzle and the material to be coated is 20-25 cm. Spray on the adhesive fine and constantly.

#### Glues:

1. permanent: Apply a thin, even coat to both surfaces. Wait for at least 10 min., then press the parts together firmly. Bonds immediately - correcting is no longer possible! The greater the pressure, the better the bonding result. The duration of the pressure is not essential for the strength of the bonding.

2. corrigible: Apply a thin, even coat to one part only and join the two parts immediately. Afterwards the position of the parts can be adjusted up to 5 min. Then the bond is permanent.

Drying time – depending on temperature and material – up to 24 h.  
One of both surfaces must be absorbent or porous!

3. removable: Apply a thin, even coat to the part that is desired to remain removable and wait for at least 20 min. Afterwards the part is self-adhesive and can be fixed and removed several times.

**Stains/residue:** For cleaning smudgy parts and equipment as well as for removing stains use cleaning spirit. Cured adhesive stains are hard to remove.

**Points of attention:** Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Throw away only when completely empty. Do not breathe vapour. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition – Do not smoke. Without adequate ventilation accumulation of potentially explosive alloys possible. Keep out of reach of children.

### TECHNICAL PROPERTIES

**Temperature resistance:** -40°C to +50°C

### TECHNICAL SPECIFICATIONS

**Appearance:** light yellow

**Chemical base:** styrene butadiene rubber (SBR)

**Density:** approx. 0,75 without fuel gas g/cm<sup>3</sup>

### STORAGE CONDITIONS

Product should be stored in a dry, cool and frost free place.

### PACK SIZES

UHU SPRAY ADHESIVE 3 in 1 is available in can of 200ml or 500ml.